
From Business Need to Testable Spec

A business need is an outcome someone wants. A functional requirement is a behavior your application delivers.



Three Terms to Anchor

Business Need

The outcome a stakeholder wants, like faster ticket triage. It states value, not behavior, and you can't code against it directly.

Functional Requirement

A specific behavior the application delivers, phrased as an input and an expected output your team can build and check.

Acceptance Criteria

The concrete conditions that prove a requirement is met, written so a developer codes to them and QA verifies them.




Start From the Outcome

Every functional requirement should trace back to a business need.

Name the outcome
the business wants in plain language first

Break it into
user-observable capabilities the app performs

Map each capability
to one Claude interaction that delivers it



Intent vs. Behavior

Business Intent

How the product should feel to the user, like fast, trustworthy, or effortless. It sets the tone but names no concrete behavior to build or test.


Functional Behavior

What the application actually does with a given input, like return a valid JSON object with the caller's name, email, and plan. That is buildable and checkable.



Decompose Into Capabilities

A big outcome hides several smaller capabilities inside it.



List each thing
a user would watch the app do

Keep every capability
observable, not internal plumbing


Size each one
so it maps to a single interaction

Three Interaction Tiers




Single call

One request in, one response out. Best for classification, summarization, extraction, or a direct question.



Workflow

A fixed, code-controlled sequence of steps you author. The path is decided at design time, not by the model.




Agent

An open-ended loop where the model chooses each next action at run time until the task is done.

Pick the Simplest Tier

Reach for the simplest tier that actually meets the need.



An agent is not your default, reach for it only when the four checks say so

Simpler tiers are cheaper, faster, and easier to test

Push up a tier only when the simpler one falls short

Four Checks Before an Agent


Before you commit to an agent, run four honest checks.

Complexity, is the task truly multi-step and hard to script?

Value, does the outcome justify the higher cost and latency?

Viability, is Claude actually capable of the open-ended task?

Cost of error, is a wrong step recoverable, not catastrophic?



Behavior or Infrastructure Driver



Looks like a behavior

A stakeholder says the app feels slow, so you write a requirement to make Claude answer faster. That reads like a functional behavior.



Really an infrastructure need

But the real driver is often a latency budget, a hosting region, or throughput. You fix that in the architecture, not by rewording the prompt.

From Need to Testable Spec



Trace every requirement back to a real business need



Tell functional behavior apart from business intent



Decompose the outcome into small, observable capabilities




Map each capability to the simplest interaction tier




Watch for behaviors that are really infrastructure constraints

Writing Functional Requirements

A good functional requirement reads like a contract.
Given this input, Claude produces this output, and here is how we check it.






Three Building Blocks

Acceptance Criteria — The specific, checkable conditions that mark a requirement as done, written so both a developer and QA read them the same way.

Input-Output Contract — A statement of what goes in and what should come back, like a schema-valid JSON object, rather than how the prompt achieves it.

Measurable Signal — An observable check that grades whether the output passed, such as valid JSON, a matching field, or a cited source.



Specify the Contract, Not the Prompt

Write the input-output contract, never the prompt itself.



Say what goes in and what shape comes back

Define exact inputs and the expected output shape.



Let structured outputs enforce a schema, not clever wording

Validate with JSON Schema so results stay consistent.



Keep implementation free to change under a stable contract

Swap models, tools, and steps without breaking consumers.

CONTRACT SEAL


Stable interface

```
GET /v1/lead-score
Response 200 OK
Input
{
   "company": "Acme Robotics",
   "industry": "Manufacturing",
   "employees": 480
}
Output (JSON)
{
   "score": 82,
   "tier": "A",
   "reasons": ["fit", "budget"],
   "confidence": 0.91
}
```

Consumers depend on this

IMPLEMENTATION DRAFT

Free to evolve



This can change anytime

A prompt is an implementation detail, the contract is the requirement.

Vague vs. Testable Criteria



Vague criteria

The answer should look good and be helpful. Nobody can code to that, and two reviewers will disagree on whether it passed.



Testable criteria

The response is valid JSON matching the schema and cites the source document. A script can grade that pass or fail every time.

Decompose the Feature

Break each feature into turns, outputs, and checks.

Turns	Outputs	Checks
1 User: "What's the weather in Paris tomorrow?"	Weather forecast for Paris tomorrow with temperature and conditions.	Has city, date, temperature in °C, and condition.
2 User: "Schedule a team standup for Friday at 10am."	Calendar event confirmed for Friday at 10:00 AM.	Has date, time, duration, and confirmation.
3 User: "Summarize my unread emails from today."	Bullet summary of unread emails today with senders and topics.	Each item has sender and topic, no duplicates.

List the user turns, what the person sends at each step

State the expected Claude output for each of those turns

Attach a success check that grades every output

Four Inputs to Plan For



Edge cases

Empty fields, huge inputs, or odd formats.
Decide the required behavior instead of leaving it to chance.



Refusal handling

Claude may decline unsafe requests.
Plan what your app does when the stop reason is a refusal.



Out-of-scope inputs

Requests outside the feature's job.
Define a graceful decline so scope stays bounded.



Ambiguous requests

Vague or missing details.
Specify whether Claude asks for clarification
or applies a documented default.

Refusal Handling Is a Requirement

Treat a refusal as a documented behavior, not a surprise.




A decline can arrive as a refusal stop reason, or in the reply text with a normal end_turn



Decide the user-facing message and any fallback path



Log it so you can measure how often it fires



Three Measurable Signals



Format signal

Does the output parse and match the schema? A JSON validator answers this automatically, with no human judgment needed.



Grounding signal

Does the answer cite the source it was given? Check that quoted spans actually appear in the supplied document.




Behavior signal

Did the app take the right action, like routing correctly or refusing when it should? Compare against a labeled set.

Keep Scope Bounded and Gradeable

A signal on every requirement keeps scope from drifting.



If you can't grade it, you can't tell when it's done

Unclear requirements hide completion. Gradeable items define finish lines.

Measurable requirements make scope creep visible fast

Metrics expose drift early so you can adjust before it compounds.

Each check becomes a test in your suite later

Today's acceptance checks turn into automated tests tomorrow.

Requirements Claude Can Meet




Specify the input-output contract, not the prompt

Define inputs, outputs, and constraints precisely so the behavior is clear and verifiable.



Make every criterion testable, never vague

Convert goals into objective pass-fail checks with unambiguous evidence.



Decompose features into turns, outputs, and checks

Break complex work into ordered steps with expected outputs and validations at each step.



Treat edge cases and refusals as first-class requirements

Enumerate known risks, harmful requests, and failure modes with explicit expected responses.





Map each requirement to a measurable signal

Link every requirement to an observable metric, log, or event that proves it’s met in production.

Budgets Before Architecture

Every real Claude application answers to more than its features.






Two Kinds of Requirement

Functional Requirement

States what the application must do, the behaviors derived from a business need. It answers what the user actually gets from the feature when everything works.

Infrastructure Requirement

States what the solution architecture must provide, the compute, latency, throughput, and hosting that support those behaviors. It answers what the system needs underneath to deliver them.



Four Constraint Families



Latency

How long a user or caller will wait for a response before the design fails them.



Throughput

How many requests per minute the integration edge has to sustain at peak.



Region and Residency

Where the calls run and where the data lives, when contracts or regulations pin a geography.



Cost

The spend ceiling per request or per month that the design has to stay inside.

Setting a Latency Budget

A latency budget is a number, not a vibe. Name it before you choose a design.

Decide the worst-case response time a user will accept

Subtract your own network and processing overhead

What's left is the budget the model call has to fit inside

A tight budget rules out multi-step loops and big contexts



Response Time Budget

Total	1.200 s
Network overhead	− 0.180 s
App / processing	− 0.270 s
Model call budget	= 0.750 s
Available for model call	0.750 s

Sync, Streaming, and Batch




Synchronous

A single request and response where the caller waits for the whole answer. Simplest to build, but the user feels the full latency.



Streaming

Tokens arrive incrementally over one connection, so the user sees output start almost immediately even when the full answer takes longer.




Batch

Many requests submitted together and collected later, trading real-time speed for lower cost on work no one is waiting on.

Throughput at the Edge

Throughput is where a design meets rate limits and concurrency reality.



Rate limits cap how many requests and tokens you get per window

A rate-limit response means slow down and retry after a wait

Backpressure means queueing work when demand outruns capacity

Sizing concurrency to the limit keeps the edge from thrashing

Region and Data Residency



First-Party API

Calls go straight to the model provider's own endpoint. Simplest path, but you inherit whichever regions that endpoint serves.



Cloud-Hosted Deployment

Claude runs inside a major cloud platform you already use, which can pin traffic to a specific region to satisfy data-residency rules.

Cost as an Architecture Driver

Sometimes the budget that binds hardest is the bill, not the clock.

Token cost
scales with context size
and number of turns

A tight cost envelope
can forbid a design outright

When volume is high,
caching stops being optional

Deferrable bulk work
belongs in a cheaper
batch lane

Monthly Cost Envelope


$7,500 of $10,000 budget

75% used

Token Cost	Extra Turns	Caching	Batch Lane
$3.1k	$2.8k	$1.2k	$0.4k
Context size Many turns	Multi-step runs High volume	Repeat context Reused prefix	Deferrable work Cheapest lane


The cost envelope constrains every choice.
Pick the mix that fits within the envelope.

Three Levers to Hit Budget




Prompt Caching

Reuse a stable prefix so repeated reads bill at a fraction of the base input price, cutting both cost and time to first token.



Message Batches

Run deferrable work asynchronously at half the standard price, collected within a day rather than in real time.



Right-Sizing

Match the model tier to the task so you never pay for reasoning the workload does not actually require.

Budgets Shape the Build



Name a latency budget, then pick sync, streaming, or batch



Plan throughput around rate limits, retries, and backpressure




Region and residency can push where the calls run




Caching and batching are requirements when the cost ceiling is tight

Does the Design Actually Fit

A design that looks elegant can still miss the requirement.





What Architecture Fit Means

Fit is a verdict, not a feeling. You either satisfy each constraint or you don't.

List every stated constraint before you evaluate anything

Write down all must-haves: latency, region, cost, availability, security, compliance, scale.

Check the design against each one in turn


Validate the design line by line. No skipping. No assumptions.

A single unmet constraint means the design does not fit

It only takes one miss to fail. Ship it and you own the risk.

Elegance never excuses a missed latency or region target

Pretty diagrams don't save outages. Targets are non-negotiable.



Requirement Check

Constraint	Requirement	Status
P95 Latency	< 300 ms	PASS
Region	us-east-1	PASS
Data at Rest	Encrypted	PASS
Availability	> 99.95%	PASS
Monthly Cost	< $25k	PASS
Max Users	100k RPS	FAIL

Design Does Not Fit

Constraint not satisfied: Max Users (100k RPS)
Fix before approving.

Three Reliability Requirements



Availability

The share of time the application has to be usable. A target here forces you to plan for the moments the primary path is down.



Failover


A defined path to a backup when the primary call fails, so one outage doesn't take the whole feature down with it.



Degradation

A reduced but still useful experience when full service isn't possible, instead of a hard error in the user's face.

Three Failover Building Blocks



Fallback Model

Route to an alternate model when the primary is unavailable, keeping the feature alive at reduced capability.



Retry With Backoff

Re-send a transient failure after a growing delay, since rate limits and server blips clear on their own.



Graceful Degradation

Return a cached, simpler, or partial answer so the user gets something useful instead of an error.

Transient vs Permanent Errors



Transient

Timeouts, rate limits, and server blips that clear on their own. The right response is a retry with exponential backoff, since waiting usually resolves them.




Permanent

Bad requests, invalid schemas, and auth failures that won't clear on retry. These need a fix, a fallback, or escalation to a human before the call can work.

Fallbacks and Degradation Paths

Reliability lives in what happens when the happy path breaks.



Decide the fallback model
before an outage forces the choice

Give the client a degraded path,
not a blank screen

A cached or simpler answer
often beats a hard failure

Match each recovery to the
error type you actually hit

Reading a Requirement for Fit

Turn each stated requirement into a question the design has to answer.

Latency budget?

Count the sequential calls in the design

Throughput target?

Check it against the rate limits


Residency rule?

Confirm where the calls actually run

Availability target?

Find the failover path or admit there isn't one

Example System: Order Fulfillment Service




Three Fit Failures



Over-Provisioned

Reaching for real-time capacity when the work is deferrable, paying premium latency and cost for speed nobody needs.



Under-Provisioned

Shipping with no failover or headroom, so the first rate-limit spike or outage takes the whole feature down.




Wrong Placement

Ignoring a residency or region constraint, so the design is technically fine but legally or contractually unusable.

A Fit Checklist

Make fit a habit by walking the same short checklist every time.



Write down every constraint, functional and infrastructure

Trace the design against each constraint, one at a time

Flag any constraint the design can't clearly satisfy

Fix, or record the tradeoff, before you call it done

A design fits only when nothing on the list is left unanswered.

Judging Architecture Fit



Reliability needs availability, failover, and degradation planned



Retry transient errors, fix or fall back on permanent ones




Read each requirement as a pass-or-fail question




Over, under, and misplaced provisioning are the common misses

Develop and Implement

Every Claude application moves through four life-cycle phases,
and the first two turn an idea into shipped software.





The Four Life-Cycle Phases



Develop

Prototype prompts and integrations against the Messages API, proving the idea works before you harden anything.



Implement

Wire auth, secrets, error handling, and deployment so the prototype runs in its target environment.



Operate

Run it in production, watching latency, token usage, error rates, and refusal or failure signatures.



Maintain

Migrate models, version prompts and schemas, and regression-test every upgrade against a frozen evaluation set.

Inside the Develop Phase

In the develop phase, you're proving the idea, not hardening it yet.

Prototype prompts directly against the Messages API

Wire a rough integration and confirm Claude returns what you need


Iterate on the prompt against real and adversarial inputs



Speed and learning matter more here than production polish.

Three Request Essentials

Endpoint	Every call is an HTTP POST to the v1 messages endpoint, sending JSON and receiving JSON back.
x-api-key	The header that authenticates the request. Keep the key in a secret manager, never hard-coded in source.
anthropic-version	A required header that pins the request and response behavior to a dated API version.



Prototype vs. Harden



Prototype


In develop, you move fast and accept rough edges. You test prompts and tweak wording because the goal is proving the idea can work at all.

Harden

Before implement, you lock the pieces down. You add validation, error handling, retries, and stable configuration so the same call behaves predictably every time.

Inside the Implement Phase

The implement phase wires your prototype into the real environment.



Move secrets into a secret manager, out of source control

Add error handling and retries for rate limits and timeouts

Set up deployment and configuration for the target platform

Now the same request runs reliably outside your laptop.

Three Things to Wire



Auth and secrets

Store the API key in a secret manager and load it at runtime, never commit it to the repo.



Error handling

Catch rate-limit and server errors, back off, and retry so one hiccup does not crash the flow.



Deployment

Package the app, set its configuration per environment, and deploy it to the target platform.


Handling Errors at the Edge

Every network call can fail, so plan for it at the integration edge.

A 429 means you're rate-limited, so back off and retry

5xx codes are server-side, and usually safe to retry

A 401 is bad auth, which retrying will never fix



RETRY HANDLER


```python
import time
import anthropic
client = anthropic.Anthropic()
delay, max_delay = 1, 32
for attempt in range(5):
    try:
        response = client.messages.create(model="claude-opus-5", max_tokens=1024, messages=[{"role": "user", "content": "Hello"}])
        break
    except anthropic.RateLimitError:
        time.sleep(delay)
        delay = min(delay * 2, max_delay)
else:
    raise RuntimeError("Request failed after retries")
```

What Goes in Source Control

Shared config — CLAUDE.md and the project settings.json are committed so the whole team gets the same behavior.

Personal config — Your settings.local.json stays gitignored. It holds machine-specific overrides that should not be shared.

Pinned model ID — Commit an exact model ID so a teammate's run behaves like yours. From 4.6 on, the dateless ID is already the pinned snapshot.



From Prototype to Shipped



Develop proves the idea against the Messages API



Implement wires auth, secrets, errors, and deployment



Handle rate limits and server errors at the edge



Commit shared config and pin an exact model ID

Operate and Maintain

A shipped Claude application is not finished. The last two life-cycle phases keep it healthy and current in production.

Operate (Monitor & Respond)

Watch the live system and act on issues fast.

Users	Req / min	Latency p95	Success rate
8,432	1,247	632 ms	99.62%

System Health

99.6% Healthy

Services	12 / 12
Tools	23 / 24
API Errors (5m)	3
Failed Jobs (1h)	7

Alerts

Tool timeout	weather_api	2m ago
High latency	/chat	5m ago
Recovery complete	embed_service	12m ago

Recent Activity

14:42:11	Job sync_users completed	12.4s
14:41:58	Retry succeeded: search_index	3.1s
14:41:37	Tool timeout: weather_api	12.0s
14:41:12	Deploy v1.27.3 rolled out	100%

Maintain (Improve & Evolve)

Measure, learn, and make the system better.

Quality score	Goal success	Eval pass rate	Cost / 1K req
4.72 / 5	92.3%	96.1%	$0.183

Top Improvements

Reranker quality	+0.18
Response relevance	+0.13
Latency p95	−41 ms
Hallucination rate	−0.7%

Recent Changes

14:35	Prompt v42 deployed
14:10	Tool schema updated
13:50	Eval set refreshed
13:20	Knowledge base synced
12:45	Feedback batch processed

Next Actions

Review alerts · Run evaluations · Ship improvements

Three Signals to Watch



Latency

How long each call takes end to end. Rising latency is often your first sign of trouble.



Token usage

The input and output tokens each call reports, which drive both your cost and your latency.



Error and refusal rate

How often calls fail or Claude declines, a direct read on your app's real-world health.

Reading Failure Signatures

Not every failure looks the same, so learn to read the signatures.

A 429 is rate limiting, a signal to slow down

Too many requests in a window triggered the limit. Back off and retry after the suggested wait.


A refusal stop reason flags a safety decline, though Claude can also decline in text with a normal end_turn

The model decided the request is unsafe or disallowed. No amount of retrying will change that decision.

max_tokens means the reply was cut off mid-answer

The response hit the maximum token limit before finishing. Increase the limit and ask Claude to continue.

Failure Signature: Rate Limiting



Retry after: 23 seconds
Client should wait and retry

JSON Response

```
{
  "type": "error",
  "error": {
    "type": "rate_limit_error",
    "message": "Rate limit exceeded for this organization."
  },
  "request_id": "req_011CSHoEeqs5C35K2UUqR7Fy"
}
```

Tip: Implement exponential backoff with jitter and respect `retry-after`.

Attempt 1 (1s) → Attempt 2 (2s) → Attempt 3 (4s) → Attempt 4 (8s) → Attempt 5 (16s)

Operate vs. Maintain

Operate

Keeping the live system healthy right now. You watch latency, token usage, and error rates, and you respond to incidents as they happen day to day.


Maintain

Keeping the system current over time. You migrate to new models, version prompts and schemas, and regression-test upgrades so change never breaks production.



Inside the Maintain Phase

Maintenance is the phase people forget, but a live app is never static.





Model migration when a version is deprecated or improved




Prompt and schema versioning so changes are reviewable



Regression testing every upgrade against a frozen set

Plan for this work, because the platform will keep evolving.

Three Facts About Model IDs



Pinned snapshot

A model ID like claude-opus-4-8 is a fixed snapshot, not an evergreen pointer to the newest model.



New model, new ID

Anthropic never changes an existing ID's weights. An improved model always ships under a brand-new ID.



Weights stay fixed

The weights are frozen per ID, but serving infrastructure can change, so watch for small behavior drift.

Migrating to a New Model

Model migration is real maintenance work, not a one-time setup task.

A deprecation of an old model or legacy mode forces the move


Platforms retire models as capabilities shift forward, requiring teams to update integrations and validate behavior.

Regression-test the new model against a frozen evaluation set

Lock inputs and expected outcomes, run both models, and measure differences across key metrics.

Compare outputs, then cut over only when quality holds

Define quality gates for acceptable deltas and monitor after rollout to catch regressions early.



Treat a model change like any code change that could regress.

The Feedback Loop


Observe — Production surfaces real latency, cost, refusals, and failures your test set never showed during the build.

Feed back — Those observations flow back into your requirements, sharpening what the app actually has to handle.

Iterate — The next cycle updates prompts, schemas, and error handling, and the loop begins again.

Versioning Prompts and Schemas

Prompts and schemas deserve the same discipline as your code.



Track each prompt in source control, tied to a model version

Version your output schema so downstream code stays in sync

Re-run a frozen eval set before shipping any change

A prompt edit can regress behavior just like a code edit.

Keeping It Alive in Production



Operate by watching latency, tokens, and error rates

Monitor key signals continuously to detect issues early and keep users happy.



Read failure signatures like 429, refusals, and max_tokens

Identify patterns fast and triage root causes before they impact more users.



Maintain by migrating models and versioning prompts

Evolve safely with versioned prompts and model updates behind feature flags.



Regression-test every change against a frozen set

Catch unintended side-effects with automated evals on a stable benchmark set.

The Messages API Request

Every call to Claude runs through one endpoint. This lesson breaks down the request you send and the alternating user and assistant turns.

1 POST /v1/messages

https://api.anthropic.com

Headers

x-api-key	sk-ant-••••••••••••
anthropic-version	2023-06-01

Body (JSON)

```
{
  "model": "claude-opus-5",
  "max_tokens": 1024,
  "system": "You are a precise assistant.",
  "messages": [
    { "role": "user",
      "content": "Summarize the
        attached sales data." }
  ]
}
```

Claude Messages Endpoint

2 Alternating Conversation

1. user — What were Q1 sales by region? → Request Sent
2. assistant — Here are the Q1 sales by region... → Response Received
3. user — Which region grew the most? → Request Sent
4. assistant — The West region grew by 18%... → Response Received
5. user — Thanks! → Request Sent

Three Required Fields



model

The Claude model that answers the request, named as a string. It picks the capability tier your call runs on.



max_tokens

The ceiling on how many tokens the reply can use. The response stops once it reaches this cap.



messages

The ordered array of conversation turns. It carries the full exchange the model reasons over for this call.

How Turns Alternate

The messages array holds the conversation as an ordered list of turns.



Each turn tags a role, either user or assistant

Every message has a role field that tells who said it.



The very first turn has to be a user turn

Conversations must begin with the user.



Two same-role turns in a row merge into one

Consecutive messages from the same role are combined.



String or List of Blocks



Plain string content

The simplest form. A turn's content is just text, fine for a quick single-message prompt with nothing else attached to it.



List of content blocks

The richer form. Content becomes an array of typed blocks, so one turn can mix text with images and tool results in a single call.

Blocks the Content Carries




text

Plain words in a turn, the most common block on both sides of the conversation.



image

A picture you attach to a user turn for the model to analyze alongside text.



tool_use

A block Claude emits naming a tool and the input it wants your code to run.




tool_result

The block you send back carrying that tool's output, tied to its request by id.

The Stateless Contract

The API keeps no memory of past calls, so state lives entirely in your request.

You send the full history each time



You resend the full conversation history every single time

Each request must include the entire message history from the beginning.

The server treats each call as brand new

It does not remember previous messages or responses.

Dropping earlier turns erases what the model knows

If you remove parts of the history, that context is lost forever.

CONVERSATION HISTORY

```python
import anthropic
client = anthropic.Anthropic()
messages = [
    {"role": "user", "content": "What's the weather?"},
    {"role": "assistant", "content": "22C"}
]
messages.append({"role": "user", "content": "And tomorrow?"})
response = client.messages.create(
    model="claude-opus-5", max_tokens=1024,
    messages=messages,
)
```

Echoing Turns Back




Echo prior turns

You rebuild each request by appending the last assistant reply and your new input onto the running array.



Keep blocks intact

Pass assistant blocks back as structured blocks, not flattened into a plain string that loses their type.



Why it matters

Flattening drops tool and thinking blocks, and the next call breaks when the model looks for them.

Where the System Prompt Sits

The system prompt is a top-level field, separate from the messages array.




It sets role, tone, and standing rules for the whole call

It defines how the model should behave across every message in the conversation.



It is not a user or assistant turn

It is configuration, not a message in the conversation history.



You pass it as a string or a list of text blocks

You can provide a single string or multiple text parts.

Request Body (JSON)

```
{
  "system": [
    {"type": "text",
     "text": "You are a helpful coding assistant."},
    {"type": "text",
     "text": "Follow the style guide and prefer clarity."}
  ],
  "messages": [
    {
      "role": "user",
      "content": "How do I paginate results
         using the API?"
    },
    {
      "role": "assistant",
      "content": "Use the page and limit
            query parameters..."
    }
  ],
  "model": "claude-opus-5",
  "max_tokens": 1024
}
```



Top-level system prompt



Conversation messages array



Other request parameters

System vs. Message Content



System prompt

Top-level instructions that persist across the whole request. It shapes behavior across the call but is not part of the turn-by-turn exchange itself.



Message content

The actual back-and-forth. User turns carry your inputs and assistant turns carry Claude's replies, each as blocks the model reads in order.

Building a Valid Request



Set model, max_tokens, and messages on every call

Always include the model to use, a max token limit, and the messages array.



Order turns so the first is always a user turn

Conversations must begin with a user message and then alternate with assistant turns.



Let content be a string or a list of typed blocks

Use a plain string for simple text or an array of content blocks for rich text, images, and attachments.





Keep the system prompt top-level, outside the turns

Place the system instruction in its own field, not inside the messages array.


Reading the Response Object

Once Claude replies, your code has to read the result correctly.
This lesson covers the response object and its content blocks.





Reading a Response Object



content

The list of blocks Claude returned. You loop over it and handle each block by its type rather than grabbing the first one.



stop_reason

A single field naming why the model stopped this turn. Your code branches on it to decide what happens next.



usage

The token accounting for the call. It reports how much input and output the request consumed for cost tracking.

Walk content by Block Type

The response content is a list, so read it by looping, not by index.

Branch on each block's type field as you go


Every item in content can be a different block type. Check the type and handle it accordingly.

A thinking or tool_use block can come first

Assume nothing about order. Your code must handle any valid sequence.

Grabbing the first block blindly will eventually break

Hard-coding an index will fail as soon as the response shape or order changes.



Common stop_reason Values



end_turn

Claude finished its reply on its own. Take the text and you're done with this call.



max_tokens

The reply hit your output cap mid-stream. Raise the cap, or continue it in a follow-up request.



tool_use

Claude paused to ask for a tool. Run it and return the result to continue.




refusal

Claude declined the request on safety grounds. This is the one case that fills in stop_details.

The tool_use Access Loop

When stop_reason comes back as tool_use, you're in a short data-access loop.




Read the tool_use block
for the tool name and input

Run that tool
inside your own application code

Append a tool_result block
and call the API again


The loop repeats until stop_reason is end_turn instead.

end_turn vs. tool_use



end_turn

The model is finished. Read the final content, stop the loop, and hand the answer back to whoever originally asked for it.



tool_use

The model paused for you. Execute the requested tool, append the result as a tool_result, and re-call so Claude can keep going.

The usage Object




input_tokens

The uncached input tokens the call billed. It counts only the remainder that was not served from cache.



output_tokens

Every token the model generated in its reply. This is the part your max_tokens ceiling limits.



cache fields

Separate counts for tokens written to and read from the cache. Add all three input figures for the full prompt size.

Guarding stop_details

The stop_details field carries extra context, but only in one situation.

It’s populated only when
stop_reason is refusal,
on Fable 5 and Opus 5

For every other stop reason
it comes back null

Reading it blindly
risks a null error

Null guard conditional check safety





```
if (response.stop_reason === "refusal") {
  const details = response.stop_details;
  console.log(details.explanation);
  console.log(details.category);
} else {
  // stop_details is null for all other reasons
  handleNonRefusal(response.stop_reason);
}
```

Passing Blocks Back Unchanged



Thinking blocks

When the reply includes thinking, pass those blocks back unmodified on the latest assistant turn, keeping the signature and everything intact.



Tool blocks

Carry tool_use and tool_result blocks forward exactly as they were. Editing or dropping any of them makes the very next call fail.

Reading Responses Cleanly

Practical rules for handling structured outputs from an agentic system.



Loop over content and branch on each block's type



Read stop_reason to decide whether to stop or act



Run the tool and re-call when it says tool_use



Check usage to keep token cost in view

Streaming SSE and Vision Input

Two features make Claude feel responsive and multimodal.

Streaming SSE

Real-time tokens over Server-Sent Events




```
event: content_block_delta
data: {
  "type" : "content_block_delta",
  "delta" : {"type": "text_delta", "text": "The"}
}
```

```
event: content_block_delta
data: {
  "type": "content_block_delta",
  "delta": {"type": "text_delta", "text": " weather"}
}
```

```
event: content_block_delta
data: {
  "type": "content_block_delta",
  "delta": {"type": "text_delta", "text": " in SF"}
}
```

```
event: message_delta
data: {
  "type": "message_delta",
  "delta": {"stop_reason": "end_turn"}
}
```


Client UI (live rendering)

The ⟶ The weather ⟶ The weather in SF

```python
import os, anthropic
client = anthropic.Anthropic(api_key=os.environ["ANTHROPIC_API_KEY"])
with client.messages.stream(
    model="claude-opus-5", max_tokens=512, messages=messages
) as stream:
    for text in stream.text_stream: print(text, end="")
```

Vision Input

Images become tokens Claude can reason over




The SSE Event Sequence

Turn on streaming with stream set to true, and events arrive in a fixed order.

message_start opens the response with an empty-content message

content_block_start, then a run of content_block_delta pieces, then content_block_stop

message_delta carries the stop_reason and usage, then message_stop ends it



STREAMING EVENT TRANSCRIPT

```
event: message_start
data: {"type": "message_start","message":{"id":"msg_01","role":"assistant","content":[]}}
event: content_block_start
data: {"type": "content_block_start","index": 0, "content_block":{"type":"text"}}
event: content_block_delta
data: {"type": "content_block_delta","index": 0, "delta":{"text":"Hello, world!"}}
event: content_block_stop
data: {"type": "content_block_stop","index": 0}
event: message_delta
data: {"type":"message_delta","delta":{"stop_reason":"end_turn"}}
event: message_stop
data: {"type":"message_stop"}
```

Reading the Stream Safely



Empty first event

message_start gives you a message with no content yet, so never try to read text from it.



Accumulate deltas


Each content_block_delta is only a fragment, so you append them to build up the full block.



Final metadata


The message_delta near the very end is where the stop_reason and usage totals arrive.

Streaming Tool Calls




input_json_delta

The delta type used when a tool_use block streams.
Its arguments arrive as partial JSON fragments.



partial_json

The field on each delta holding a piece of the
argument text. You concatenate the pieces as they come.




content_block_stop

The moment you parse the accumulated JSON.
The final tool input is always a complete object, never a string.

When to Stream

Streaming changes the experience, not the answer, so pick it deliberately.



Reach for it on long outputs so users see progress instead of waiting


---

It lets you render text token by token in a live interface

One limit to know, streaming is unsupported inside the Batches API


For large bulk jobs that run async, you give up streaming.

Three Image Source Types



base64

Inline image data encoded as base64, paired with a media_type like image/png. This works everywhere.



url

A link to an image the system fetches for you. It keeps your request payload small.



file_id

A reference to an image you uploaded through the Files API, reusable across turns without resending.

Formats and Placement

Claude reads the common web image formats, with a few habits worth forming.

Supported formats are JPEG, PNG, GIF, and WebP

Claude can read these web image formats.

Animations aren't processed, only the first frame is read


If an image is animated, Claude uses just the first frame.

Place images before the text that refers to them for best results

This helps Claude connect the right image to the right context.



Image Limits and Cost




Max dimensions

Any single image can be up to 8000 by 8000 pixels before it is rejected.




Max file size

Up to 10 megabytes per image as base64 on the Claude API.



Visual tokens

Claude reads images in 28 by 28 pixel patches, and each patch costs one visual token.




Resolution tiers

Newer models like Opus 4.8 handle a longer edge, up to 2576 pixels, than older ones.

What Vision Won't Do

Vision means understanding images, and it comes with real boundaries.



Claude reads image content, but it can't generate or edit images

It doesn't read hidden metadata, and it won't name people in a photo

Counting and exact spatial positions come back approximate, not precise

Streaming and Vision Recap



Streaming events run message_start to message_stop in order




A streamed tool_use assembles from partial JSON into one object



Streaming isn't available inside the Batches API




Images pass as content blocks via base64, url, or file_id




Vision understands images, but never generates or edits


Adaptive Thinking and Effort

Newer models changed how reasoning depth works.






Three Thinking Concepts



Adaptive thinking

The current path, set with thinking type adaptive and no budget_tokens. Claude decides when and how much to think.



effort

The reasoning-depth control, nested at output_config.effort. Values run low, medium, high as the default, xhigh, and max on the current frontier models.



Legacy budget_tokens

The older mode, thinking type enabled with an explicit budget. It is mid-deprecation and rejected on the newest models.

Thinking Defaults by Model

On Opus 4.8 and Opus 4.7, adaptive is the only on-mode, and it is off by default.

Omitting the thinking field
on those two runs the request without any thinking

You turn it on explicitly
with thinking type **adaptive**

On Sonnet 5, adaptive
runs by default, pass thinking type **disabled** to turn it off

Toggle model reasoning

OFF

Default for Opus 4.8 and Opus 4.7

Opus 4.8	Opus 4.7	Sonnet 5
Default OFF	Default OFF	Default ON

- OFF — Disabled
- ON — Enabled
- Adaptive — Only on-mode

Setting Reasoning Effort

Reasoning depth is a separate control from turning thinking on.




effort is nested at output_config.effort, not at the top level

Values run low, medium, high as the default, xhigh, and max

xhigh is available on Fable 5, Opus 4.8, Opus 4.7, and Sonnet 5


Keying effort at the request root is a common mistake.

Adaptive vs. Legacy budget_tokens



Adaptive


Set with thinking type adaptive and no fixed budget. Claude sizes its own reasoning. This is the current path on the newest models.



Legacy budget_tokens

Set with thinking type enabled and an explicit token budget. It returns a 400 on Fable 5, Sonnet 5, Opus 4.8, and Opus 4.7.

Why Name the Model



Rejected

budget_tokens returns a 400 error on Fable 5, Sonnet 5, Opus 4.8, and Opus 4.7 today.



Transitional

On Opus 4.6, budget_tokens still works as a deprecated escape hatch during model migration.



Still required

On Sonnet 4.5 and Opus 4.5, budget_tokens is still the only way to enable thinking.


thinking.display Controls Visibility

On the newest models, thinking blocks are hidden by default.

thinking.display defaults to omitted on Fable 5, Opus 4.8, Opus 4.7, and Sonnet 5

Set it to summarized to surface a readable summary of the reasoning

Visibility does not change billing, thinking is billed the same either way



Multi-Turn Thinking Rules

Pass blocks back unmodified

During multi-turn or tool use, thinking blocks in the latest assistant message go back exactly as returned.

redacted_thinking


Encrypted reasoning Claude returns when content is filtered. It carries opaque data and needs the same care.

Modifying breaks it

Editing a thinking or signature block in the latest turn returns a 400 on the next call.

Thinking Plus Tool Use

Turning thinking on narrows your tool_choice options.



With extended thinking and tools, only auto or none are allowed

When extended thinking is enabled alongside tools, the tool_choice can only be auto or none.

Forcing a call with any or a named tool returns an error

Attempting to force tool execution with any or a specific tool name is rejected with an error.

The latest assistant thinking blocks still travel back unmodified

Thinking blocks in the assistant response are preserved and returned exactly as produced.

Plan your tool loop around these two constraints together.

Adaptive Thinking Essentials



On Opus 4.8 and Opus 4.7, thinking is off unless you set it



effort lives at output_config.effort, defaulting to high



Legacy budget_tokens is mid-deprecation, so name the model



Extended thinking with tools allows only auto or none



Pass thinking blocks back unmodified in the latest turn

Prompt Caching Breakpoints

Long, stable context that repeats on every call is expensive to reprocess. Prompt caching fixes that by reusing a marked prefix.

This lesson walks through how breakpoints mark that prefix, the two TTLs you can choose, and when the cost math actually pays off.



Three Caching Concepts



Prompt caching

Reusing an already-processed prefix by marking it, so a large, stable context is not reprocessed on every call.



cache_control breakpoint

An explicit marker on a block. Up to four per request, each ending a cacheable prefix at that point.



Cache TTL

How long an entry lives. A 5-minute ephemeral window is the default, with a 1-hour option available.

The Prefix Match

Caching matches on an exact prefix, in a fixed render order.



The prefix runs tools, then system, then messages

The model processes the prefix in a fixed order: tools first, then system, then messages.



The cache key is the exact rendered bytes of that prefix

The cache key is computed from the precise bytes of the fully rendered prefix.



Any byte change anywhere in the prefix invalidates everything after it

Even a single byte difference causes a cache miss for everything that follows.

1



Tools

Ordered

```
1. get_weather   { location: "San Francisco" }
2. search_docs   { query: "refund policy" }
3. get_user      { user_id: "u_12345" }
...
```

2



System

Single

```
You are a helpful assistant.
Use the tools when needed.
Answer concisely and accurately.
...
```

3



Messages

Multiple

```
user: What's the weather in SF tomorrow?
assistant: { "type": "tool_use", "name": "get_weather" }
user: { "type": "tool_result", "content": "18 C, Cloudy" }
user: Also, what's your refund policy?
...
```


The prefix (cacheable)

Placing Breakpoints

You mark cacheable boundaries with cache_control breakpoints.

Example Request Flow

Breakpoints mark cacheable boundaries



Each breakpoint creates a reusable, deterministic prefix.
Later steps can change without invalidating earlier caches.

You get up to four explicit breakpoints per request

Define up to four cache_control breakpoints to segment the request into reusable prefixes.

Place them at stability boundaries, where content stops changing

Breakpoints should align with the points where inputs become stable and deterministic.

A breakpoint on the last system block caches tools and system together

The final breakpoint captures the entire static system state along with tool definitions for maximum reuse.

5-Minute vs. 1-Hour TTL



5-minute TTL

The default ephemeral window, active unless you ask for the longer one. Each read refreshes the entry, so steady traffic keeps a hot prefix alive cheaply.



1-hour TTL

Set with type ephemeral and ttl one hour.
It survives longer gaps between calls,
but it carries a higher write cost.

Cache Cost Multipliers




Cache read

A hit costs 0.1x of the base input price, so reuse is where the savings come from.



5-minute write

Writing a 5-minute entry costs 1.25x of base input, a small one-time premium.



1-hour write

Writing a 1-hour entry costs 2.0x of base input, the price of the longer window.

When Caching Pays Off

Caching only saves money when a prefix is reused enough.

It pays off when
a stable prefix dominates the request size

Cheap 0.1x reads
have to outweigh the one-time write premium

A 5-minute entry
pays for itself after roughly one reuse

Break-even scale: reads outweigh write cost



Write vs read cost

1x write cost = 10x reads at 0.1x each

Example



Cached for 5 minutes



Roughly one reuse pays for the write

Minimum Cacheable Prefix



Per-model minimum

The prefix has to clear a token floor to cache.
It's 1,024 tokens on Opus and Sonnet, 2,048 on Haiku.



Below the floor

Shorter prefixes silently do not cache.
You get cache_creation_input_tokens zero and no error at all.



Model-scoped

The minimum varies by model, and caches don't carry across models.
A model switch is a full miss.

Verifying Cache Hits

You confirm caching is working by reading the usage fields.

```
Call 1
 cache_creation_input_tokens:   4128
 cache_read_input_tokens:       0

Call 2
 cache_creation_input_tokens:   0
 cache_read_input_tokens:       4128 ✓
```

A zero here on Call 2 means the cache was hit

Check cache_read_input_tokens on repeated identical-prefix calls

A steady zero across repeats means a silent invalidator crept in

Common culprits are a datetime stamp, unsorted JSON, or a shifting tool set

Freeze the prefix and the reads show up where you expect.

Making Caching Pay Off



The prefix runs tools, system, then messages, byte-exact



Place up to four cache_control breakpoints at stable spots



Reads cost 0.1x, 5-minute writes 1.25x, 1-hour writes 2.0x




A prefix clears a per-model token floor to cache



Verify hits with cache_read_input_tokens

Realtime vs. Batch: Going Async

Claude gives you two ways to send requests, one immediate and one asynchronous.




Two Ways to Reach Claude



Synchronous Messages API

You send a request and block for the response. It's the right call for interactive, latency-bound flows, and it's the only surface that streams tokens back as they generate.



Message Batches API

You submit many requests as one asynchronous job. Claude processes them in the background at fifty percent of standard price, trading immediacy for a large discount on bulk work.

Three Batch Fundamentals



Batches endpoint

You post a batch to the batches endpoint. Each entry pairs a custom_id with params, a normal Messages request body.



Fifty percent price

Both input and output tokens bill at half the standard rate, the core reason the Batches API exists.



Asynchronous

You don't wait on the call. You submit, poll for completion, then retrieve every result together later.

The 50% Cost Tradeoff

The discount is the whole point of going async.

Both input and output tokens bill at half the standard price

The savings scale with volume, so bulk jobs benefit most

In exchange, you give up an immediate response and streaming



Batch Timing Windows



Best-effort speed

Most batches finish in under an hour, but that's best-effort, not a guaranteed service level.



24-hour processing

A batch has to complete within 24 hours. Requests that outlive that window expire and go unbilled.



Results ready

Results become available when every request finishes, or at the 24-hour mark, whichever comes first.

Processing Window vs. Retention



24-hour processing window

This is the deadline to finish the job. Miss it and the unprocessed requests expire, unbilled. It governs whether your batch completes at all.



29-day retention window

This is how long finished results stay downloadable, 29 days after creation. After that the batch is still viewable, but you can no longer pull results.

Batch Limits and Constraints

One batch holds a lot, but hard ceilings apply.

Batch Capacity Ceilings

256 MB
Max Payload

100K
Max Requests



Up to 100,000 requests in a single batch



Or 256 megabytes of total payload, whichever you hit first



Batches are also not eligible for Zero Data Retention

BATCH SUBMIT

```python
import anthropic
client = anthropic.Anthropic()
response = client.messages.batches.create(requests=batch_requests)
batch_id = response.id
```

When Realtime Wins

Reach for the synchronous Messages API when speed is the requirement.

A user is waiting on the response in real time

The person expects an immediate reply and sees it as it arrives.

You want to stream tokens as they generate

Partial output appears token by token to reduce perceived latency.

The work is interactive and latency-bound

The task is turn-based or conversational where delays hurt the experience.

If someone or something blocks on the answer, stay realtime.



When Batch Wins

Reach for batches when volume matters more than immediacy.



Large offline workloads
like evals or bulk classification

Document processing
where no one waits on each result

Any latency-insensitive job
where the 50% discount pays off

Choosing Your API Surface



Synchronous Messages API for interactive, streaming, latency-bound work



Message Batches API for large offline jobs at half price



Most batches finish under an hour, but it's best-effort




The 24-hour processing window is not the 29-day retention window

Batch Jobs: custom_id and Results

Once you've decided to batch, you need to run one correctly.

This lesson covers the shape of a batch request, the custom_id that keys every entry, and why results come back unordered.

It also covers which parameters do and don't carry from the synchronous API into a batch.



Inside a Batch Request



custom_id

A unique label you assign to each request in the batch. It's how you'll match a result back to the input that produced it.



params

The standard Messages request body for that entry, model, max_tokens, messages, and everything a normal call takes.



Uniqueness

Every custom_id has to be distinct within the batch. Reusing one makes results ambiguous and breaks the mapping.

The custom_id Rules

custom_id has a strict format you have to respect.



One to sixty-four characters, no longer

The identifier must be between 1 and 64 characters.



Only letters, numbers, hyphens, and underscores are allowed

Use only uppercase or lowercase letters, 0-9, hyphens (-), and underscores (_).



It has to be unique within the batch

No two custom_id values in the same batch can be identical.

EXAMPLES

```
order_1042
invoice_2025_05_17
row-57-customer-record
```

Illustrative only - any name that follows the rules works.

VALIDATION CHECK



Length
1-64 chars



Allowed
a-z A-Z 0-9 - _




No spaces
or other symbols



Not unique
within the batch


Pick something meaningful, like a row ID, so matching later is easy.

Match by ID, Not by Position



Match by custom_id

The correct pattern. Each result carries the custom_id you assigned, so you look up the input by that key, no matter what order results arrive in.




Match by position

The trap. Assuming the third result lines up with the third input corrupts your data, because batch results are not returned in submission order.

Results Come Back Unordered

This is the gotcha to watch with batches.



Results can arrive in any order, not submission order

Positional matching silently corrupts your mapping

Always look up each result by its custom_id

What Still Works in a Batch



Vision

Image inputs work normally. A batch can process vision requests just like the synchronous API does.



Tool use

Client tools and every server tool are supported, including web search, web fetch, and code execution.



System and multi-turn

System messages and full multi-turn conversations carry over into a batch without any changes.



Extended thinking

Adaptive thinking runs in batches too, and legacy extended thinking on the older models that still accept it.

What a Batch Won't Accept


A short list of parameters gets rejected inside a batch.

stream is out, batches never stream

speed, the fast-mode flag, isn't allowed


Thread params like store and cache hints are rejected

And **max_tokens** has to be at least one, never zero



Caching in a Batch

Prompt caching still works in batches, with one caveat.



Requests run concurrently, in any order, so caching is best-effort

A short cache lifetime may expire before related requests run

Prefer the 1-hour cache lifetime for shared context in a batch

That keeps a common prefix warm across the whole job.

Three Batch Gotchas to Remember



Unordered results

Results don't follow submission order. Match every one by custom_id, never by position, or your data silently misaligns.



Limited params

stream, speed, thread, and cache-hint params are rejected, and max_tokens has to be at least one.



Still full-featured

Tool use, vision, system messages, and thinking all work, so batches aren't a stripped-down mode.

BATCH RESULTS

```
for result in client.messages.batches.results(batch_id):
    if result.result.type == "succeeded":
        text = result.result.message.content[0].text
        outputs[result.custom_id] = text
```

Running a Batch Correctly



Every request pairs a custom_id with a standard params body



custom_id is one to sixty-four characters, unique in the batch




Match results by custom_id, because order is never guaranteed




Tool use, vision, and thinking work, streaming and a few params don’t

Invoking Claude on Amazon Bedrock

Amazon Bedrock lets you reach Claude through your existing AWS account instead of the first-party API.





Bedrock Delivery Basics



Same Messages API

Bedrock accepts the identical request body and returns the same streaming events, so your prompt and parsing code stay unchanged.



bedrock-mantle

The current endpoint for Opus 4.7 and later, matching the first-party body shape and standard streaming behavior.



AWS Credentials

You authenticate with AWS access rather than an Anthropic key, using roles or tokens from your own account.

The Current Bedrock Path

The modern integration is the bedrock-mantle Messages API, reached through your chosen AWS region.




It uses the same request body and standard streaming as the first-party API



You install the Bedrock extra for your language SDK



The client name signals the path you are on



Your existing prompt and response code moves over with almost no change.

Current vs Legacy Integration



Current: bedrock-mantle

The Messages API with a bare anthropic. prefix on model IDs and the AnthropicBedrockMantle client. Recommended for Opus 4.7 and later.



Legacy: InvokeModel

The older InvokeModel or Converse calls with global./us. profile IDs and the plain AnthropicBedrock client. Available for Opus 4.6 and earlier.

Model IDs on Bedrock

On Bedrock, model identifiers carry a bare anthropic. prefix that differs from the first-party names.

Model Identifier Naming

Required prefix | Model family | Model version

`anthropic.` `<model-family>` - `<version>`

Current format

`<scope>` `.anthropic.` `<model-family>` - `<version>`

Legacy format


Inference routing

- global
- us

→ Anthropic Models

Model families

- claude-opus
- claude-sonnet



Examples include
anthropic.claude-opus-4-8 and anthropic.claude-sonnet-5




The legacy path
instead uses profile-prefixed IDs like global.anthropic. and us.anthropic.



Picking the wrong prefix
for your client is a common setup error

Match the prefix to the client, or the request will fail.

AWS Credential Precedence




Constructor Arguments

Credentials passed directly to the client take highest priority and override everything else.



Environment Variables

Next, the SDK reads AWS access key, secret, session token, and region from the environment.



Config and Chain

Last, it falls back to your AWS config file and the standard credential chain.


Authentication Options

Bedrock gives you three ways to authenticate, all built on AWS access rather than an Anthropic key.

A Bedrock service role
is the recommended default

IAM assumed roles
work with a twelve-hour maximum session

Bearer tokens
share the twelve-hour maximum but are static credentials, the least preferred option



Whichever you pick, no Anthropic API key ever enters the request.

Feature Gaps to Remember

No URL or Files API

Image and document sources have to be inline base64 on Bedrock, capped at five megabytes per image.

No Server Tools

Code execution, web search, and web fetch do not run on Bedrock, so avoid designing around them.

No Batches or MCP

The Message Batches API and the MCP connector are also unavailable on this vendor surface.

What Carries Over

Plenty still works on Bedrock, so most core application patterns move without change.

Supported Features That Carry Over

- Prompt caching and extended thinking both function normally
- Client-side tool use, citations, and structured outputs are supported
- Global and Regional endpoints exist, with Regional adding a ten percent premium

Why It Matters in Practice

Deeper reasoning stays enabled: Use extended thinking and maintain context across long tasks without changing your approach.

Your tools and data keep working: Call APIs, query data, and enforce structure with the same client-side patterns.

Predictable reach, predictable pricing: Choose Global for lowest cost or Regional for data residency, accepting the ten percent premium.

Design to the supported set and your Bedrock app behaves like the first-party one.

Bedrock in Practice



Current path is bedrock-mantle with bare anthropic. model IDs



InvokeModel with global./us. profile IDs is the legacy path



Authenticate with AWS credentials, never an Anthropic key




Files API, server tools, and batches are unavailable



Caching, thinking, and tool use still carry over

Invoking Claude on Google Vertex AI

Google Vertex AI is another major way to reach Claude from a cloud account, this time inside Google Cloud. The Messages API is almost identical, but two request details move, and authentication looks different. This lesson covers those differences and the features Vertex does and does not support.





Vertex Delivery Basics



Nearly the Same API

Vertex uses the Messages API with only two request-format changes, so most of your code carries straight over.



Model in the URL

Instead of the request body, the model identifier is named directly in the endpoint URL you call.




Google Cloud Auth

You authenticate with Google Cloud credentials, not an Anthropic API key and not an x-api-key header.

Two Request Differences

Vertex keeps the Messages API but moves two specific pieces of the request.

REQUEST STRUCTURE DIFF



WHAT THIS MEANS

The model identifier lives in the endpoint URL, not the request body

Vertex determines the model from the endpoint path. The request body no longer includes a model field.

The anthropic_version field goes in the body and equals vertex-2023-10-16

Use anthropic_version with the exact value "vertex-2023-10-16". Other values will be rejected by the API.

Get these two right and the rest of the request looks completely familiar.

The Endpoint URL

On Vertex, the model you want is encoded into the path you call.



The path names your project, location, and the publisher anthropic




The model ID sits near the end, before the rawPredict action



For the model choice, only the endpoint changes. The rest of the body stays familiar

URL path structure



Example endpoint

```
https://aiplatform.googleapis.com/v1/projects/my-project/
locations/global/publishers/anthropic/models/claude-opus-5:rawPredict
```

Because the model lives in the URL, each model is a separate endpoint.

Version and Authentication



anthropic_version

A body field that has to equal the literal string vertex-2023-10-16, never a header and never a made-up value.



Google Cloud Credentials

You sign in with application-default login or a bearer access token, the same way other Google Cloud services authenticate.



No Anthropic Key

There is no x-api-key header and no Anthropic API key on Vertex, which surprises many first-time users.

Region Choices



Global

The recommended region value, with no added premium and the widest current-model coverage.



Multi-Region

The us or eu values keep data in a broad area and add a ten percent premium.



Specific Region


A value like us-east5 pins one location and also adds a ten percent premium.

Model IDs on Vertex

Vertex names models two ways, depending on whether you want the current generation or a fixed snapshot.

Two ID formats

Current model ID (no date)



Dated snapshot ID (with version)



Key points

Current models use the bare first-party ID, like claude-opus-4-8

Dated snapshots use an @ version separator, like claude-opus-4-5@20251101

Bedrock vs Vertex



Amazon Bedrock

Model IDs carry a bare anthropic prefix and sit in the request body. You authenticate with AWS credentials through the AnthropicBedrockMantle client.



Google Vertex

The model ID lives in the URL while anthropic_version goes in the body. You authenticate with Google Cloud credentials through the AnthropicVertex client.

Feature Gaps and One Exception

Vertex shares most of Bedrock's feature gaps, with one notable exception.


URL image input, the Files API, and the MCP connector are unavailable

The Message Batches API does not run on Vertex either

Web fetch and code execution are not supported

One Exception: Web Search

Vertex supports web search in its basic variant only.




```
WEB SEARCH TOOL CALL
from anthropic import AnthropicVertex
client = AnthropicVertex(project_id="my-project", region="global")
response = client.messages.create(
    model="claude-opus-5",
    max_tokens=1024,
    tools=[{"type": "web_search_20250305", "name": "web_search"}],
    messages=[{"role": "user", "content": "Latest renewable energy news"}],
)
```

Vertex in Practice



The model ID lives in the endpoint URL, not the body



anthropic_version goes in the body as vertex-2023-10-16



Authenticate with Google Cloud credentials, never an Anthropic key



Batches, Files API, and MCP are out, but basic web search works

REST Fundamentals for the Claude API

The Claude API is a plain HTTP REST interface, the same kind of web API you have called many times before.

This lesson covers the REST basics, the verbs and headers you send, and the status codes you read back on every call.



REST in Three Core Ideas




Client-Server

The client and the server stay independent. Your code calls the API, and the API owns the model behind it.



Stateless

Every request carries all its own context. The server keeps no memory of past calls, so you resend the full conversation.



Uniform Interface

Resources sit behind URLs and you act on them with standard verbs. One predictable pattern covers the whole API surface.

One Endpoint, One Verb

For the core of the Claude API, almost everything you do is a POST to a single messages endpoint.

HTTPS

You call POST on the /v1/messages path over HTTPS

All requests use HTTPS and the POST method on a single path.


The same endpoint handles every model you target

Switch models without changing the URL or the integration.

{ }

You pick the model inside the body, not the URL

The model parameter in the JSON body decides which model processes the request.



One verb, one path, and the request body does the rest.

Safe vs Idempotent



Safe

A safe method does not change server state. A GET only reads, so you can call it freely without side effects on the resource.



Idempotent

An idempotent method gives the same result whether you call it once or many times. A repeated DELETE lands the resource in the same state.

HTTP Methods at a Glance

Across REST APIs, a handful of verbs cover the common actions on a resource.

	**GET**	Retrieve a representation of the target resource.
	**POST**	Create a new resource or trigger a server-side action.
	**PUT**	Replace the target resource with the request payload.
	**PATCH**	Apply partial modifications to the target resource.
	**DELETE**	Remove the target resource; repeating has no effect.



GET reads a resource and never changes it



POST creates or triggers a non-repeatable action



PUT fully replaces, while **PATCH** updates part



DELETE removes, and repeats land the same way

The Claude messages call is a POST, since each generation is a fresh action.

Four Status Code Families



2xx Success

The request worked. 200 means OK and your response body is ready to parse.




3xx Redirect

The resource moved. You rarely handle these directly against the Claude API.



4xx Client Error

Something in your request is wrong. Auth, formatting, or rate limits usually cause it.



5xx Server Error

The fault is on the server side. Retry with backoff rather than changing your request.

Headers You Send on Every Call

A Claude request needs a few headers before the body even matters.



x-api-key carries your secret API key for auth



anthropic-version pins the dated API behavior



content-type is application/json for the body

`POST` `https://api.anthropic.com/v1/messages`

Headers

```
x-api-key: sk-ant-abc123def456ghi789jkl0
anthropic-version: 2023-06-01
content-type: application/json
accept: application/json
```

Body

```
{
   "model": "claude-opus-5",
   "max_tokens": 1024,
   "messages": [ ... ]
}
```

Miss the version or the key, and the call fails before Claude ever runs.

Status Codes You Will Debug



401 vs 403

A 401 means you are not authenticated, usually a bad or missing API key. A 403 means authenticated but not allowed.



429 Too Many

A 429 means you hit a rate limit. Slow down and retry with backoff rather than hammering the endpoint.




400 Bad Request

A 400 means your body is malformed or invalid. Fix the request itself before you retry, since a repeat will fail the same way.

SDKs Wrap the Same REST Calls

The Anthropic SDKs are convenience clients over this exact REST surface.



Every SDK method becomes one of these HTTP calls

High-level methods map to specific endpoints.

The SDK sets your headers, auth, and retries for you

Authentication, timeouts, and retry logic are handled automatically.

It parses the JSON so you work with typed objects

Raw JSON responses are converted into typed, easy-to-use objects.

SDK CALL - PARSE JSON

```python
import json, anthropic
client = anthropic.Anthropic()
response = client.messages.create(
    model="claude-opus-5", max_tokens=1024,
    messages=[{"role": "user", "content": "Summarize as JSON."}])
data = json.loads(response.content[0].text)
print(data["summary"])
```

Nothing the SDK does exists beyond what the raw API already supports.

REST Foundations to Keep



You POST to one messages endpoint over HTTPS

All requests use HTTPS to a single /v1/messages endpoint.



x-api-key and anthropic-version headers are required

Every request must include both headers for authentication and versioning.



Status families tell you success, client, or server faults

2xx means success, 4xx means client error, 5xx means server error.



401 is auth, 403 is permission, 429 is rate limits

These specific codes map to auth, access, and rate limiting issues.



SDKs wrap these same calls with no hidden powers

Client libraries simply handle request construction and responses.

JSON Request and Response Bodies

Once you know the REST shape, the real work is the JSON body you send and the JSON body you read back.

REQUEST BODY

POST /v1/tasks

```
{
  "title": "Generate weekly sales report",
  "description": "Summarize key metrics
   and trends for leadership.",
  "priority": "high",
  "scheduled_for": "2025-05-23T09:00:00Z",
  "tags": [ "sales", "weekly", "leadership" ],
  "parameters": {
    "region": "North America",
    "start_date": "2025-05-16",
    "end_date": "2025-05-22",
    "currency": "USD"
  },
  "notify": {
    "email": true,
    "channels": [ "slack", "email" ]
  },
  "options": {
    "include_charts": true,
    "format": "pdf",
    "row_limit": 1000
  },
  "metadata": {
    "request_id": "req_8f3a7c15",
    "correlation_id": "corr_91d2b7"
  }
}
```

RESPONSE BODY

200 OK

```
{
  "task_id": "task_2b9e4f7d",
  "status": "scheduled",
  "created_at": "2025-05-21T14:32:10Z",
  "scheduled_for": "2025-05-23T09:00:00Z",
  "result_location": {
    "type": "s3",
    "bucket": "reports-prod",
    "key": "sales/weekly/2025-05-23/report.pdf",
    "expires_at": "2025-06-06T09:00:00Z"
  },
  "estimated_duration_seconds": 180,
  "notifications": [
    { "type": "slack", "channel": "#reports" },
    { "type": "email", "to": "team@acme.com" }
  ],
  "summary": {
    "records_processed": 124532,
    "charts_generated": 8,
    "warnings": []
  },
  "links": {
    "self": "/v1/tasks/task_2b9e4f7d",
    "cancel": "/v1/tasks/task_2b9e4f7d/cancel"
  }
}
```

JSON in Three Building Blocks



Objects

Curly-brace collections of key and value pairs. The whole Claude request is one object, with keys like model and messages inside.



Arrays

Ordered lists in square brackets. The messages array holds your turns in order, and content itself is an array of blocks.



Scalars

The simple values: strings, numbers, booleans, and null. These fill leaf fields like a message's text or a token count.

The Request Body Top Level

Every Claude request is a single JSON object with a few required keys.



model names which Claude version you want



messages is the array of your conversation turns



max_tokens caps how long the reply can run

Optional keys like system, temperature, and tools round out the body.

REQUEST BODY

```
{
  "model": "claude-opus-5",
  "system": "You are a concise computer science tutor.",
  "messages": [
    {  "role": "user",
       "content": "Explain what a binary search tree is." },
    {  "role": "assistant",
       "content": "A binary search tree keeps smaller keys left." },
    {  "role": "user",
       "content": "Now show me an insert example." }
  ],
  "max_tokens": 512
}
```

Inside the messages Array



Role

Each turn has a role, either user or assistant, marking who is speaking.



Content Blocks

Content is a list of typed blocks, not a plain string. A block can be text, an image, tool_use, or tool_result.



Order Matters

Turns are read in array order, so append each new message to the end to keep the thread coherent.

Three Parts of the Response




content

An array of output blocks. Text lives in a text block's text field, ready to pull out and display.



stop_reason

Why generation ended: end_turn, max_tokens, tool_use, or stop_sequence. It tells your code what to do next.




usage

Input and output token counts for the call. You read these for cost tracking and context budgeting.

Parsing the Response in Code

Reading a Claude response means walking the JSON, not grabbing one string.



Loop the content array and find the text blocks

The content array can mix text, tool_use, and other block types. Extract only the text blocks.

Check stop_reason before you trust the output

A stop_reason other than "end_turn" means the message may be incomplete or cut off.

Pull token counts from usage for your logs

Track input_tokens and output_tokens to monitor cost and performance.

Treat the body as structured data and parsing stays predictable.

Request Body vs Response Body



Request Body

What you send up: model, the messages array, max_tokens, and optional params like system and tools. You control every field in it.



Response Body

What comes back: a content array of blocks, a stop_reason, usage token counts, and metadata such as the message id and model version.


Encoding and Body Size

JSON is plain text, which shapes how you handle large or binary content.

content-type is **application/json**, and the body is UTF-8 text

Images and files go in as base64-encoded strings

base64 inflates size, so large bodies grow fast



Watch request size when you pack in multimodal content.


From JSON to Objects in Code

In your code, that JSON becomes native objects you can navigate directly.

JSON (string)

```
{
  "user": {
    "id": 42,
    "name": "Ada Lovelace",
    "email": "ada@example.com",
    "roles": ["admin", "editor"],
    "profile": {
      "timezone": "UTC",
      "preferences": {
        "theme": "dark",
        "language": "en-US"
      }
    }
  },
  "active": true,
  "signup_date": "2025-05-01"
}
```

Parsed Native Objects



dict · list · nested dict · str · int · bool

A JSON object maps to a dict or a typed class

Key-value pairs become dictionary entries or class attributes.

Arrays become lists you loop over

JSON arrays convert to lists, so you can iterate and process each item.

Nested blocks become nested fields you index into

Nested objects become nested dicts or attributes you can access with dot or key notation.

The SDK does this mapping, handing you typed objects instead of raw text.

JSON Bodies to Remember



Objects, arrays, and scalars build the whole body



The request carries model, messages, and max_tokens



The response returns content, stop_reason, and usage




Message content is a list of blocks, not a string




Images ride in as base64, so watch body size

Async and Await for API Calls

Network calls to Claude spend most of their time waiting, not computing.




Blocking vs. Non-Blocking Calls



Blocking call

Your code stops on the request and waits for the full response before the next line runs. One slow network call freezes everything behind it.



Non-blocking call

You issue the request and await it, so the event loop runs other work while the response is in flight. The caller never sits idle.

Three Async Building Blocks



Coroutine

A function you define with async that can pause at an await and hand control back, then resume where it left off.



Event loop

The scheduler that runs coroutines, and while one waits on the network, it advances another that’s ready.



await

The keyword that suspends a coroutine until its awaited result is ready, without blocking the whole thread.

Why Network Calls Fit Async

A Claude request is I/O-bound, it waits on the network far more than it uses the CPU.



Most of the call is idle
waiting for bytes to arrive




That idle time is free
for other work to run



Async reclaims it
without extra threads

Async Claude Request Timeline





Active CPU time
~80 ms (6%)



Idle waiting time
~1,170 ms (88%)



Receiving time
~80 ms (6%)

Total wall-clock time: ~1,330 ms

How await Frees the Caller

When you await a Claude call, the coroutine pauses and the loop moves on.





Control returns to the event loop at the await point

Your coroutine yields, and the runtime regains control immediately.



Other ready coroutines run while the response is pending


The loop schedules other work instead of waiting idle.



Your coroutine resumes the moment the result lands

The awaited result is delivered back to your code, and execution continues.

Two Async Misconceptions



Async equals parallel

It doesn't. On a single thread, async interleaves tasks and only one runs at a time between the await points. The work overlaps, but nothing runs simultaneously.



Await means blocking

The opposite is true. An await is exactly the point where your code yields control, letting the loop run other ready work while this call waits.


Anatomy of an Async Call

Here's the shape of a single non-blocking request end to end.

You call the async client method and get back a coroutine


You await it, and the loop parks your task

The response arrives and your code resumes with the result




One call, no frozen thread, no busy waiting.

Concurrency vs. Parallelism vs. Async




Concurrency

Structuring work so many tasks are in progress at once, taking turns, even on a single thread.



Parallelism

Actually running tasks at the same instant on multiple cores, which needs more than one thread.




Async

One way to get concurrency, using an event loop and await rather than many threads.

Common Async Pitfalls

A few habits turn async code back into blocking code by accident.



Calling a blocking library
inside a coroutine stalls the whole loop

Forgetting to await
leaves a coroutine that never runs

Doing heavy CPU work
on the loop freezes every task

Keep the loop free to do what it's good at, waiting.

Non-Blocking by Default



Blocking calls freeze the caller, non-blocking calls free it



The event loop runs other work while a request is in flight




await marks the pause point where control yields



Async gives concurrency on one thread, not true parallelism

Concurrency, Streaming, Backpressure

Issuing one Claude call without blocking is the easy part. The real work is running many at once, safely.



Fanning Out Concurrent Requests

When you have many independent Claude calls, you don't have to run them one by one.



Start every request
so they're in flight together

Kick off all Claude calls at the same time so none of them wait on others.




Await them as a group
and collect all the results

Use a group await to gather results once every call finishes.



Total time trends toward
your slowest call, not the sum

You wait for the longest-running call, not the total of all calls.




```
const results = await Promise.all([
    claude.messages.create({ model, max_tokens, messages: msgA }),
    claude.messages.create({ model, max_tokens, messages: msgB }),
    claude.messages.create({ model, max_tokens, messages: msgC }),
    claude.messages.create({ model, max_tokens, messages: msgD }),
    claude.messages.create({ model, max_tokens, messages: msgE }),
]);
```

Three Concurrency Tools



Gather

A call that starts many coroutines together and waits for all of them to finish, returning results as a set.



Semaphore


A counter that caps how many requests run at once, forcing the rest to wait their turn.



Bounded parallelism

Running concurrently, but only N at a time, so you stay under limits instead of flooding the API.

Unbounded vs. Bounded Fan-Out



Unbounded fan-out

You launch all requests at once. It's simple, but a big batch instantly blows past your rate limit and triggers a wave of 429 errors.



Bounded fan-out

You cap concurrency with a semaphore, keeping only so many in flight. Slightly more code, far more reliable under real load.

Consuming a Streamed Response

With streaming on, the response arrives as an async iterator of small events.





You loop over events with async for as they land

The client exposes an async iterator. Each iteration yields the next event as soon as it's received.



Text arrives as deltas, small pieces you append in order

Content arrives in content_block_delta events. Extract the text delta and append it to your buffer in order.



You keep accumulating until the content block completes

When you receive content_block_stop, the block is complete and the full text is ready to use.

Staying Under Rate Limits




Rate limits

The API caps requests and tokens per minute. Exceed them and you get a 429 Too Many Requests.



Backpressure

Let the slowest stage set the pace, so you stop submitting faster than results drain.



Semaphore

Cap in-flight requests to a fixed number, holding new work until a slot frees up.



Retry with backoff

On a 429, wait and retry with exponential backoff rather than hammering immediately.

Retry With Backoff


Transient failures are normal at scale, so plan to retry them.

Retry transient errors, timeouts, 429s, and 5xx blips

Wait longer after each try with exponential backoff

Add random jitter so retries don't all fire at once

Don't retry a permanent error, a bad request won't fix itself.



RETRY EXAMPLE


```python
import anthropic, time, random
client = anthropic.Anthropic()
for attempt in range(5):
    try:
        resp = client.messages.create(
            model="claude-opus-5", max_tokens=1024, messages=msgs)
        break
    except anthropic.APIStatusError as e:
        time.sleep((2 ** attempt) + random.uniform(0, 1))
```

Concurrent Calls vs. the Batches API



Async concurrency

Many real-time calls at full price, bounded by your rate limit. You reach for it when a user or downstream system needs answers back now.




Batches API

One asynchronous job at half price. Most batches finish within the hour, and 24 hours is the ceiling. It fits bulk work when nobody is waiting on any single result.

Error Isolation Across Branches

When you fan out, treat each call's failure as its own, not the whole job's.




Gather results
so one failure
doesn't cancel the rest

Capture each branch's
outcome, result
or exception

Handle or retry
the failures
after the group returns

Concurrency Under Control



Fan out independent calls so they run in flight together



Cap in-flight work with a semaphore to respect rate limits



Consume streamed deltas with async for until the block completes




Isolate failures and retry transient errors with backoff

Version Control for Claude Apps

A Claude application is source code, and that source belongs under version control. This lesson covers the core git moves you already use.


Git Workflow




```
$ git status
On branch main
Changes to be committed:
  new file:    agents/support_agent.yml
  modified:    tools/search_docs.py
Untracked files:
  workflows/escalation.flow
```

```
$ git add .
$ git commit -m "Add escalation workflow"
$ git push origin main
$ git log --oneline -3
a1b2c3d Add escalation workflow
9f8e7d6 Update search tool
4c3b2a1 Initial commit
```

Repository Structure



Three Git Building Blocks



Commit

A saved snapshot of your files, named by a content hash. The same hash always points to the exact same state.



Branch

A movable pointer to a line of work. You branch to develop a change in isolation before merging it back.



Tag

A fixed label on one commit, used to mark a release so you can find and rebuild that exact version.

Why Version a Claude App

Putting the whole app in git buys you the same safety net as any codebase.




Every change has an author, a time, and a message

Every version records who changed what, when, and why.



You can roll back a bad prompt in seconds


Revert to any previous version instantly and safely.



History shows exactly when behavior shifted

See the precise version where outputs started to change.

Version history



Safety net




Recover instantly

No manual cleanup

Full audit trail


No changes lost

Merge vs. Rebase



Merge


Combines two branches and records a merge commit. History keeps every branch as it happened, which is honest but can look tangled.



Rebase

Replays your commits on top of another branch for a straight line. The history reads cleaner, but you're rewriting commits, so avoid it on shared branches.

The Feature Branch Flow




Branch

Cut a branch off the main line so your work stays isolated from everyone else's.



Commit

Save small, focused commits with clear messages as you build the change.



Open a request

Push the branch and open a pull request so teammates can review the diff.




Review and merge

After review and passing checks, merge it back into the main line.

What Counts as Source

For a Claude app, source is more than application code.




The prompts that shape every model response

The tool and output schemas you define

The config files that set behavior and permissions


All of it is text, so all of it can and should live in git.

Reviewing a Change




Pull request

A proposed set of commits opened for review before it merges. It's the gate where a change gets a second set of eyes.



Diff

The line-by-line view of what changed. For a prompt, the diff shows the exact wording that shifted.



Code review

A teammate reading the diff to catch defects, unclear logic, or risky wording before it lands.


Diffing a Prompt Change

The real win for a Claude app is that prompt edits become reviewable.



A reworded instruction shows up as a plain diff

Small prompt edits are surfaced clearly, so everyone can see exactly what changed.



Reviewers see the behavior shift before it ships

Review diffs alongside example inputs and outputs to catch unintended changes.



History pins exactly which commit changed a response

Every response links back to the specific commit, author, and time of the change.

A prompt tweak gets the same scrutiny as a code change.

Prompt: customer_support_triage

Before (Commit a1b2c3d)

```
You are a support assistant.
Answer the user's question
using our knowledge base.
If you don't know, say you're
not sure.
```

After (Commit e4f5g6h)

```
You are a support assistant.
Use the knowledge base to
answer the user's question.
If information is missing,
ask one clarifying question
before responding.
```

Review: Behavior shift

Test case	Before output	After output
User: "Why was I charged twice?"	"I'm not sure."	"I need a bit more info. What date were the charges on?"


Approve

History

Commit	Author	Time	Changed	Impact
e4f5g6h	alex	2025-05-14 10:32	Lines 2-6 (added)	Output changed
a1b2c3d	maya	2025-05-10 16:08	Lines 4-5 (removed)	Output changed


Same Rigor for Both

Code changes and prompt changes both shape outcomes. Review both with the same discipline.



Application code

You'd never merge a code change without review. Bugs slip in when a change lands unread, so the branch-and-review flow guards it.



Prompt and config

Treat these identically. A one-line prompt edit can swing model behavior more than a code change, so it earns exactly the same review.

Git as the App's Backbone



Commits, branches, and tags track every change



Prompts and schemas are source, not loose text




Pull requests put a second set of eyes on each diff



Prompt edits get the same review as code

Config in Source Control

A Claude app behaves the way its config tells it to, so that config travels with the code.



Committed vs. Gitignored Config



Committed (team-shared)

Project CLAUDE.md and the project settings file belong in git. Everyone who clones the repo gets the same instructions and permissions by default.



Gitignored (personal)

Your local settings file and personal CLAUDE.local.md stay out of the repo. They hold individual tweaks that shouldn't override a teammate's setup.

Why Shared Config Ships

Committing config isn't bureaucracy; it's how a team gets one consistent Claude.

Everyone pulls the same instructions and permissions


Shared config keeps prompts, tools, and guardrails aligned across every environment.

A new teammate is productive right after cloning

Clone the repo, set one key, and the system just works the same way for everyone.

Behavior is reproducible, not machine-by-machine luck

Versioned config ensures the same inputs and rules produce the same results every time.



Shared config means the app acts the same on every desk.

Three Things You Check In



CLAUDE.md

The project instructions that shape how Claude works in this repo, shared with the whole team.



settings.json

The project settings file holding permissions, hooks, and the model choice for everyone.




Prompts and schemas

The system prompts and tool schemas your app depends on, versioned right beside the application code.

Pinning the Model ID

One config value deserves special care, the model ID you call.



Each model ID is a fixed snapshot, not a moving target

Pinning it in config keeps the same weights over time

A new model ships under a new ID, never silently

Commit the exact ID so every run and teammate hits the same model.

The Three SemVer Parts



MAJOR

The first number. You bump it for a breaking change, one that isn't backward compatible with what came before.



MINOR

The middle number. You bump it when you add functionality that stays backward compatible with older callers.



PATCH

The last number. You bump it for a backward-compatible bug fix that changes no behavior on purpose.


Moving Through the SDLC

Version control plugs your Claude work into the normal delivery stages.


Develop a change on a branch, config and prompts included

Review the diff so behavior shifts are caught early

Test and gate the change, then deploy the merged result




Tracked vs. Untracked Change



Tracked change

The prompt or config edit lives in a commit. There's a diff, an author, a reason, and a way to roll it back cleanly if it misbehaves.



Untracked change

The edit happens in a chat window or a personal file. Nobody can see it, review it, or reproduce it, and drift creeps in quietly.

CI Checks on Config



Validate config

A CI step parses your settings and CLAUDE.md so a broken file is caught before it merges, not in production.



Check schemas

The pipeline validates tool and output schemas against their spec, so a malformed schema fails the build early.



Gate prompts

Automated checks can diff and lint prompt changes, flagging risky edits for a human before the merge goes through.

Config as Shared Truth



Commit project CLAUDE.md and settings, not personal files



Pin the exact model ID for stable weights



Version prompts and config with semantic versioning



Let CI validate config before every merge

Reviewing Claude Integration Code

Integration code that calls Claude deserves the same review rigor as any other application code.

Pull Request #248

Open — feat: integrate Claude into report generator

Files changed | Conversation 3 | Checks All good

- src/
  - services/
    - claudeClient.ts +142
    - types.ts +18
    - prompt.ts +67
  - tests/
    - claudeClient.test.ts +89
  - .env.example +12

src/services/claudeClient.ts +142

```
1   import Anthropic from "@anthropic-ai/sdk";
2   const client = new Anthropic({
3     apiKey: process.env.ANTHROPIC_API_KEY,
4   });
5
6   export async function getReport(summary: string) {
7     const resp = await client.messages.create({
28  +     model: "claude-opus-5",
29  +     max_tokens: 1200,
30  +     thinking: { type: "adaptive" },
31  +     messages: [{ role: "user",
32  +                  content: buildPrompt(summary) }],
33  +   });
-   -       return resp.content[0].text;
-   -     }
```

Reviewer comment — 2h ago

Consider retry logic for rate limits and timeouts.

Claude Integration Review

Checklist for safe, reliable, and maintainable code

- **Secrets & Config** — No hardcoded keys. Use env vars.
- **Model & Params** — Correct model. Appropriate params.
- **Prompt & Data** — Validate inputs. No sensitive leakage.
- **Error Handling** — Retries, backoff, and timeouts.
- **Logging & Monitoring** — Structured logs. Track usage & errors.
- **Access Control** — Least privilege. Secure endpoints.

Three Review Focus Areas



Error Handling

Reviewing whether the code classifies each failure by type first, then retries transient errors and fixes or escalates permanent ones.



Response Validation

Checking the model response against a schema or rules after generation, and re-prompting with the error on failure so it can correct.



Defensive Parsing

Consuming output with code that anticipates malformed or incomplete content, so one bad generation never crashes the pipeline.

Reviewing Error Handling and Retries

Start with how the code reacts when a call fails.

Does it classify the error before reacting?


The system should understand the error type and choose the right path.

Are only transient errors retried, with backoff?

Retries should use exponential backoff and stop after a limit.

Do permanent errors get a fix or escalation, not a retry?

Permanent failures should be routed for human review, not retried blindly.



A retry loop wrapped around a bad request just burns budget and time.

One Question for Every Retry Loop



Can It Clear?

Timeouts, rate limits, 5xx, and network blips resolve on their own. These are the only errors a retry loop should touch.




Will It Repeat?

A bad request, invalid schema, or 4xx auth failure returns the same result every time.
A retry wrapped around one is a defect to flag.

Reviewing Response Validation

Confident output is still fallible, so review the validation path.



Is the response checked against a schema or business rules?

Validate structure, types, and required fields before accepting it.

On failure, does it re-prompt with the error to correct?

Return the specific error and request a corrected response automatically.

Are semantic checks there, not just a syntax check?

Verify meanings, ranges, IDs, and business invariants - not only JSON validity.

A pipeline with no correction route leaves reliability to luck.

Defensive Parsing Checks



Tolerant extraction

Read fields without assuming they are present or well-typed. Handle a missing or null value on purpose.



Explicit failure

When output surprises the parser, fail safely and loudly instead of proceeding on bad or half-formed data.



No blind trust

Even with structured outputs, downstream code should not treat a confident-looking response as a guaranteed contract.

Reviewing Prompt and Schema Changes

Prompt and schema edits change behavior, so review them like code.



Does the diff show exactly what shifted in the prompt?

Review additions, deletions, and rewording that can change model behavior.



Was the schema change checked against structured-output rules?

Validate required fields, types, enums, and constraints against the rules.



Could this quietly break a downstream parser?

Assess impact on downstream consumers and error-handling paths.

Prompt Diff

BEFORE

```
You are a helpful assistant.

Answer concisely in JSON.
```

AFTER

```
+ Be precise and include units
  where relevant.

- Answer concisely in JSON.
```

Schema Diff

BEFORE

```
{
  "type": "object",
  "properties": {
    "city": { "type": "string" },
    "temp_c": { "type": "number" }
  },
  "required": ["city", "temp_c"]
}
```

AFTER

```
{
  "type": "object",
  "properties": {
    "city": { "type": "string" },
    "temp_c": { "type": "number" },
+   "condition": { "type": "string" }
  },
  "required": ["city", "temp_c", "condition"]
}
```

Treat a wording tweak as a behavioral change, because it is.

Readability and Naming Criteria



Clear naming

Names should say what a value or function does, so a reviewer follows the integration without tracing every call by hand.



Readable structure

The request, the call, the validation, and the parse should read top to bottom, not hide inside one dense block.




Reviewable size

A change small enough to reason about is easier to approve than a sprawling edit that mixes many concerns at once.

Claude as a Review Assistant

Claude can help review, but the approval stays human.



It can flag likely defects and missing error handling

Claude inspects code changes and surfaces potential issues early.

It can summarize what a prompt or schema change does

Claude explains the impact of changes in natural language.

A person still approves every change before it merges

Human judgment and accountability stay in control.

Use it to widen coverage, not to hand off judgment.

What Good Review Catches



Classify errors first, retry only transient ones

Separate transient, throttling, and permanent failures.
Retry with backoff only for transient issues.



Validate responses and re-prompt on failure

Check structure, required fields, and constraints.
If invalid or incomplete, fix the prompt and try again.



Parse defensively, never trust confident output blindly

Treat model output as untrusted data.
Use strict parsing, defaults, and bounds checking.



Review prompt and schema diffs like application logic

Diff prompts, tool definitions, and schemas.
Small changes can cause big behavior shifts.




Let Claude assist, but keep a human approving

Claude boosts velocity and coverage.
A human owns the final decision.

Refactoring Prompts and App Code

Refactoring restructures working code without changing what it does,
and Claude integrations benefit as much as anything.



What Refactoring Means



Behavior-preserving

Refactoring restructures code to improve readability and maintainability without changing what it does. Output stays the same before and after.



Tests as safety net

Tests confirm behavior is unchanged, so you refactor with confidence. Without them, a restructuring can silently break something.



Keep changes separate

A refactor and a feature change should not share one commit. Mixing them makes review and rollback much harder.

Isolate API Calls Behind an Interface

Wrap every Claude call behind one small, clean interface.

Callers use your client, not the raw API directly

Code across your app calls your interface, not the API.


Model, headers, and retries live in one place

Centralized config ensures consistency and simplifies maintenance.

The rest of the app depends on your interface, not the SDK

You can change SDKs or settings without touching feature code.

Swapping a model or endpoint then touches a single module.



Scattered Calls vs. One Client



Scattered API calls

The model name, headers, and retry logic are copied across many files. A single change, like pinning a new model, means editing every one.




One shared client

All calls route through a single client module. A model pin, header, or retry change happens once, and every caller picks it up.

Extract Shared Prompt Fragments

Duplicated prompt text is a maintenance trap, so extract it.



Pull repeated instructions into one shared fragment

Eliminates duplication and ensures consistency across all agents.

Store reusable system prompts as named, testable units

Version, test, and manage prompts like any other code artifact.

Reference the shared fragment instead of copy-pasting

Simplifies updates and reduces the risk of drift and errors.

Common Refactoring Targets



Duplicated prompts

Repeated instruction text scattered across files. Extract it into one shared, named fragment.




Inline config

Model names and settings hard-coded at each call site. Pull them into one config module.



Repeated call logic

The same request, retry, and parse code copied everywhere. Wrap it behind one client.



Tangled concerns

Prompt building, the API call, and parsing all mixed in one function. Split them apart.

Reduce Coupling, One Place to Change

Loose coupling means one change touches one place.



A model pin update lives in the client, not every caller

Change the model once in the client and all callers use it automatically.




A prompt version bump changes one shared fragment

Update a single prompt file and every caller that references it gets the new words instantly.



A config tweak flows out from a single source

Edit one configuration value and all dependent components receive the updated setting.



When change is localized, swaps get cheap and low-risk.

Small and Large Refactors



Small refactors

Rename a variable, extract a helper, remove duplication. Low risk, done continuously as you touch the code.



Large refactors

Reshaping module boundaries or introducing a client layer. Higher risk, so lean on tests and do it in reviewable steps.



Same rule

Both preserve behavior. Neither should ride along with a feature change in the same commit.

Claude as a Refactoring Partner

Claude is a strong refactoring partner, within limits.

Spot Duplication

↓

Suggest Extraction

↓

You Review And Approve

↓

Tests Verify Behavior

Example: Extract duplicate order total calculation

```
- def calc_total(order):                  + def calculate_order_total(items):
-     total = 0                            +     return sum(i.qty * i.price for i in items)
-     for item in order.items:         ⇨   +
-         total += item.qty * item.price   + def calc_total(order):
-     return total                         +     return calculate_order_total(order.items)
```



It can spot duplication and suggest an extraction

Claude analyzes the codebase to find repeated logic and recommends extracting it into a single, reusable function or method.



It can propose a client interface for scattered calls

Claude designs a clean client interface to unify scattered API or service calls behind a consistent, easy-to-use layer.



Tests still verify behavior stayed the same

Automated tests run after changes to confirm outputs and behavior remain unchanged across scenarios.

Keeping the Integration Maintainable



Preserve behavior, and lean on tests as the safety net



Isolate API calls behind one clean client interface



Extract shared prompt fragments and config into reusable units




Reduce coupling so a model or prompt change touches one place




Let Claude assist, verify with tests, keep a human approving

One Model, Many Surfaces

The same Claude model answers whether you call the raw API, use the Agent SDK, or open Claude Code. The scaffolding around it changes.





Three Ways to Reach Claude




Raw API

The Messages endpoint you call directly, supplying every instruction yourself through the system parameter with no config auto-loaded.



Agent SDK

A library that runs the agent loop for you. Its default system prompt is minimal, not the full Claude Code one.



Claude Code

The command-line coding agent. It loads a full system prompt, the whole CLAUDE.md hierarchy, and auto memory at startup.

Same Model, Different Scaffolding

The model's core behavior is constant. The wrapper around it is what varies.



Tool access differs, from none up to a full toolset

Some wrappers expose no tools. Others unlock search, code, data, APIs, and more.




File and config loading is surface-specific

Each wrapper decides what files, configs, and context it can see.



Session and memory models are not the same everywhere

Some keep long histories, others are stateless or ephemeral by design.



Same reasoning, same behavior

SYSTEM PROMPT + MULTI-TURN MESSAGES (ANTHROPIC SDK)

```
import anthropic
client = anthropic.Anthropic()
response = client.messages.create(
    model="claude-opus-5",
    max_tokens=1024,
    system=("You are a helpful assistant. Answer accurately and concisely. "
            "Ask clarifying questions if needed."),
    messages=[
        {"role": "user", "content": "How does photosynthesis work?"},
        {"role": "assistant", "content": "Photosynthesis converts light energy..."},
        {"role": "user", "content": "What are the key reactants?"}
    ]
)
```

Tell the two apart and behavior stops feeling random.

Where Instructions Land



Raw API

Instructions go in the system parameter you set on the request. Nothing else is loaded.



Agent SDK

A minimal default prompt, plus CLAUDE.md when the matching setting sources are enabled, which they are by default.



Claude Code

A full system prompt, the CLAUDE.md hierarchy, rules, and auto memory at launch.




Hosted chat

Profile and Project custom instructions that apply only inside that web surface.

What the Raw API Gives You

On the raw API, there's no magic. You get exactly what you configure and nothing more.



PARSE STRUCTURED JSON FROM RESPONSE

```python
from anthropic import Anthropic
import json
client = Anthropic()
resp = client.messages.create(model="claude-opus-5", max_tokens=800, messages=messages)
data = json.loads(resp.content[0].text)  # Extract structured JSON
trend, change = data["trend"], data["change"]
```

The system parameter is your only instruction channel

Everything the model follows must be in the system field you send.

No CLAUDE.md, no presets, and no auto memory

There is no project context, saved preferences, or automatic recall.

Persona, safety, and tool guidance are all yours to supply

You must define behavior, constraints, and available tools explicitly.

SDK Default vs Claude Code



Agent SDK default

Runs the same agent loop, but its system prompt is minimal, built for tool calling only. To match the command-line agent you set the claude_code preset explicitly.



Claude Code

Uses the full Claude Code system prompt by default, even in headless print mode. It loads its whole config stack without you opting into anything.

How the SDK Loads CLAUDE.md


The SDK doesn't read CLAUDE.md because of a preset. Setting sources control it.

The project source loads your repo's CLAUDE.md file

The user source loads the one in your home config

Default query options enable both, so it loads automatically

Pass an empty sources list and no CLAUDE.md loads at all.



The Hosted Chat Surfaces





claude.ai


The web app where profile custom instructions and Project instructions shape every conversation, scoped to that surface alone.





Claude Desktop

A consumer chat app comparable to the web, with custom instructions and connectors. Its instruction details stay light here.





Surface scoped


Instructions set in a chat app never reach your Claude Code sessions or API calls. Each surface keeps its own.

MESSAGE HISTORY WITH CLAUDE SDK

```
import anthropic
client = anthropic.Anthropic()
response = client.messages.create(
    model="claude-opus-5",
    messages=[{"role": "user", "content": "What's our Q2 roadmap status?"}, {"role": "assistant", "content":
      "Here's the current plan..."}, {"role": "user", "content": "What are the top 3 risks?"}],
    max_tokens=512,
)
```

Isolate the Interface Layer

When behavior differs across surfaces, separate the interface from the model output.



Reproduce the same prompt on a second surface

Run the identical request on another interface to see if the behavior changes.

Check what config and tools each one actually loaded

Differences in system prompts, parameters, or tools can change the output.

Confirm the model output before blaming the model

Capture the raw model output (developer view) to verify what the model actually produced.


Most surprises trace back to scaffolding, not the model itself.

One Model, Many Wrappers



The raw API loads only your system parameter

Call the messages endpoint with system; Claude applies no wrappers.



The Agent SDK defaults to a minimal prompt

The SDK injects a compact baseline prompt and handles the loop.



Claude Code loads the full prompt and CLAUDE.md

It reads your project's CLAUDE.md and builds the complete context.





Setting sources, not the preset, load CLAUDE.md

Explicit sources determine what's loaded – presets only shape defaults.


Writing Portable Instructions

Instructions can behave differently depending on where they load. This lesson shows why that drift happens.





Where Instructions Live



System prompt

The top-level channel for standing behavior. On the raw API you set it directly, and output styles or append modify it.



CLAUDE.md

Developer-authored rules loaded into context. It is delivered as a user message alongside whichever system prompt you chose.



In-session message

An instruction you type mid-conversation. It steers the current session but persists nowhere once that session ends.

CLAUDE.md Is a User Message

Here's the key fact worth memorizing. CLAUDE.md is not part of the system prompt.

It's injected into the conversation as a user message


CLAUDE.md is sent by the user in the conversation like any other message.

It shapes behavior alongside whichever system prompt you chose

Claude follows the system prompt you selected, while also following instructions from CLAUDE.md.

Its content doesn't affect the system prompt cache

Changing CLAUDE.md won't hit the system prompt cache or invalidate it.




System Prompt vs a User Message



Writes to the system prompt

Output styles and the append option write directly into the system prompt. They change the cached prefix and apply as top-level behavior for the run.




Rides as a user message

CLAUDE.md loads as a user message beside your chosen system prompt, and it leaves the system prompt cache entirely untouched.

Why Behavior Drifts

Drift isn't the model changing its mind. It's the same words loading in different places.



One surface reads a file the next one never sees

If the file or knowledge source isn't available in that surface, the model can't use it.

A rule set in a chat app stays in that chat app

Instructions, examples, and context don't follow you to other surfaces unless you carry them.

A minimal default prompt omits what you assumed was there

Without the full context you had in mind, the model fills gaps with common but different choices.

Keeping Instructions Portable



State rules explicitly

Write the instruction where the surface will actually load it, rather than assuming an auto-load.



Commit shared rules

Put durable project rules in a committed CLAUDE.md so every teammate and surface reads the same thing.



Never trust defaults

If a rule matters, set it yourself. Don’t rely on a surface to supply it for you.


Chat Instructions Stay Put

A rule you set in claude.ai does not follow the model into your code.

Profile and Project
instructions apply only
in that web app

Claude Code and the API
never see them


Each surface
keeps its own
separate configuration



RETRY WITH BACKOFF


```python
import time, random, anthropic
client = anthropic.Anthropic()
for attempt in range(5):
    try:
        response = client.messages.create(model="claude-opus-5", max_tokens=1024, messages=messages)
        break
    except (anthropic.RateLimitError, anthropic.InternalServerError, anthropic.APIConnectionError) as e:
        if attempt == 4: raise
        time.sleep(min(2 ** attempt, 30) + random.uniform(0, 1))  # exponential backoff + jitter
```

Choosing the Right Surface



Raw API or SDK

Reach for these when you're embedding Claude in an application and want programmatic control over every request.



Claude Code

Reach for it when you're doing repo-based development and want files, tools, and CLAUDE.md loaded for you.



Hosted chat

Reach for it for quick interactive work where you don't need code, files, or a persistent integration.

Debug the Drift

When a rule seems ignored, find out whether the surface ever loaded it.

Diagnosing an Ignored Instruction



1 Check file exists and is readable

```
$ ls -l rules/role-play.md
 -rw-r--r--  1 user  staff  2.4K  May 14 10:32  role-play.md
```

2 Inspect the payload sent to the model

```
{
  "model": "claude-opus-5",
  "max_tokens": 1024,
  "system": "[System prompt ...]",
  "messages": [
    {"role": "user", "content": "[User message ...]"}
  ]
}
```

Missing role-play.md instruction

3 Diff the expected vs. actual system prompt

```
- You must always ask for clarification before answering.
+ (Missing from actual system prompt)
```

4 Fix the load, then re-run and verify

```
Loaded 12 rule files successfully.
Rule role-play.md is included.
```

Confirm the instruction reached the model at all

Trace the rule from source to the payload. If it isn't there, the model can't follow it.

Check whether it landed as system or user text

Placement changes how the model interprets importance and intent. Misplacement can nullify a rule.

Re-test the same rule on a surface you fully control

Run the rule in a minimal, known-good setup. If it works there, the issue is with the original surface.

Instructions That Travel Well



CLAUDE.md loads as a user message, not the system prompt



Output styles and append change the system prompt directly




Chat-app rules stay scoped to that surface



Put durable rules in committed config

Setting Content and Data Boundaries

Content boundaries decide which text your app treats as instructions and which it treats as data.



Boundary Design Basics



Content Boundaries

The explicit line between trusted developer instructions and untrusted external content, marked so the model treats data as data.



Untrusted Input

Anything your app did not author, such as user messages, retrieved documents, web content, or tool results.




Trusted Context

Your system prompt and developer instructions, the content you control and can hold the model accountable to.

Marking the Boundary in a Prompt

You mark boundaries structurally, using the roles and delimiters the API already gives you.



Put instructions in the system role, user and external data in the user role

Wrap retrieved documents in labeled XML tags so their edges are unambiguous

Never paste untrusted text inline with your instructions

Structure tells the model which text is authority and which is just content.

Prompt Injection vs Jailbreak



Prompt Injection

Untrusted input smuggles instructions into the context and the model follows them, hijacking what your application does.
Defended by isolation and least privilege.



Jailbreak

A direct user coaxes the model past its own safety policy to produce disallowed content.
Defended by the model's safety training, not by input handling.

Where Untrusted Input Arrives



User Messages

The obvious channel. Anything an end user types can carry an injection attempt aimed at your instructions.



Retrieved Documents

Files, pages, and knowledge-base results can hide instructions in their text, even from an internal store.



Tool Results

Output from a tool or API call is untrusted too.
An injection can ride in through a returned payload.

Scoping Data Access Per Call

Boundaries aren't only about the prompt. They're about what each call is even allowed to touch.

Give a call only the data and tools the task needs


Narrow, purpose-built access reduces risk and blast radius.

Separate what Claude may see from what it may emit

Different boundaries for input and output prevent leakage.

Minimize sensitive data on the way in, not just on the way out

Send less, summarize early, and redact before invoking.




Protecting Sensitive Data



Data Leakage

Unintended exposure of secrets, other users' data, or system-prompt contents through model output, tool arguments, or logs.



PII Handling

Minimize what you collect, then redact or tokenize personal data before it enters prompts or logs, restricting access.



Confidentiality, Integrity, Privacy


Who may read, who may change, and lawful minimal use of personal data. Injection and leakage threaten all three.

COMPLETIONS WITH LIMITS

```python
import anthropic
client = anthropic.Anthropic()
response = client.messages.create(
    model="claude-opus-5",
    max_tokens=512,
    stop_sequences=["\n\nHuman:", "<end_of_turn>"],
    messages=[{"role": "user", "content": "Summarize this ticket."}],
)
```

Validating Returned Payloads

A boundary isn't complete until you check what comes back before acting on it.



Validate every payload against its declared schema first

Parse defensively, expecting missing or malformed fields

On a bad payload, fail loudly and re-prompt, don't act on it

Even guaranteed JSON can carry a plausible but wrong value your code should catch.

Three Boundary Habits



Separate Instructions

Keep trusted instructions and untrusted data in different roles and tags so injected text never reads as a command.



Least Privilege

Give each call only the data and tools it needs, so a slip has the smallest possible reach.



Validate Output

Check every returned payload against its schema and business rules before any code acts on it.

Boundaries That Hold



Separate trusted instructions from untrusted data with roles and tags



Treat user input, documents, and tool results as untrusted




Scope each call to least privilege on data and tools



Validate every payload before your code acts on it


Managing Context and Session State

A long Claude Code session slowly fills its context window, and nothing ever leaves that window on its own.



This lesson covers what piles up as you work, what all that context costs, and how knowledge carries forward into the next session.

Three Terms for Session State



Context window

The token budget the model reads in one request. It holds the system prompt, history, tool definitions, and every tool result at once.



Durable state

Knowledge kept outside the live window, in a file or config, so it survives a truncation or the end of a session.



Session boundary

The point where one working session ends and a fresh context window begins, carrying nothing forward unless you saved it.

What Accumulates as You Work

Within one session, everything you do stacks up in the same window.

The system prompt and tool definitions ride along on every turn

They stay in context from start to finish, consuming tokens the whole way.

The full back-and-forth history keeps growing as you go

Every user message and assistant reply remains in the window.

Large tool results, files, and search output linger long after use

Big outputs and attachments stick around and add up quickly.



None of it clears itself, so the window only ever gets fuller.

Ephemeral Context vs. Durable State



Ephemeral context

Whatever sits in the live window right now. The model sees it instantly, but it vanishes the moment the window truncates or the session ends.



Durable state

Knowledge written outside the window, to a file or config. It survives compaction and session boundaries, so it is still there tomorrow.

What a Full Window Costs



Higher cost

Every token in the window is reprocessed each turn, so a bloated window means a bigger bill.



Slower responses

More tokens to read on every call adds latency, so replies take longer as the window grows.



Drift and errors

As low-signal history piles up, the model follows instructions less reliably and key context gets crowded out.

Pruning Stale Tool Output

The biggest budget-killer is old tool output you no longer need.



A giant file
you read sits in the window every later turn

A huge search result
keeps costing tokens after you have used it

Pruning drops
that single result without touching the rest

Three Facts About a New Session



Fresh context window

Every Claude Code session starts empty. The model remembers nothing from last time unless something on disk restores it.



CLAUDE.md files

Instructions you write. The project-root file loads at session start and re-injects after compaction, so durable rules persist.



Auto memory

Learnings Claude writes for itself, stored on disk under a MEMORY.md index and reloaded as needed across future sessions.


State Lives in Your Code

When you build on the API directly, the session boundary is yours to draw.

The API is stateless, so it keeps no memory between calls

Your code owns the transcript and resends it every request


Starting a new session means resetting that message history



You decide what carries over and re-ground the rest from config.

Bloat and Drift Over Long Runs

Left unmanaged, a session degrades in ways that are easy to miss.



Instruction-following weakens as low-signal tokens crowd the window

Early context gets pushed out of the model's effective attention

Costs climb steadily even when the useful content has not grown

Keeping Context Focused



The window only accumulates; nothing leaves unless you remove it



Ephemeral context vanishes; durable state lives on disk



CLAUDE.md and auto memory carry knowledge to the next session




Bloat raises cost and drives drift over long runs

Clearing, Compacting, and Starting Fresh

Sooner or later a session gets too long or wanders off task,
and the clean move is to reset. Claude Code gives you distinct ways to do that.


Reset Context Window

Start a new session with zero carryover.



Compact and Start Fresh

Keep what matters, drop the rest,
and continue with clarity.



Three Ways to Reset



Compact

Summarize the older history into a tight recap, keep recent turns and key decisions, and free up space.



Clear

Wipe the conversation and start the same session over with an empty window, dropping all prior context.



Start fresh

Open a brand new session and re-ground it from CLAUDE.md and memory when the old one has drifted.

Compact vs. Clear



Compacting

Preserves continuity. It summarizes older turns but keeps the thread going, so recent decisions and the current task survive in condensed form.



Clearing

Starts over. It empties the window completely in the same session, so nothing from the prior conversation carries forward at all. Use it when the current context is more baggage than help.

What Survives Compaction


Compaction is not lossless, so know what it protects and what it can drop.

Your project-root CLAUDE.md re-injects from disk, so its rules survive

Recent turns and key decisions are kept in the summary

Early prompt detail and nested CLAUDE.md files can fall away

Anything you need to keep should live in config, not buried in history.



Three Things a Reset Handles



Project-root CLAUDE.md

Re-read from disk and re-injected after a compaction, so its instructions persist through every reset.



Nested CLAUDE.md

Files in subdirectories are not re-injected automatically; they reload only when Claude next reads a file there.



Conversation-only notes

Anything you said in chat but never wrote down does not survive; add it to CLAUDE.md to keep it.

When to Start Fresh

Sometimes compacting isn't enough and the cleanest move is a brand new session.



The session has drifted far from the task you actually want done

Bloat has piled up faster than pruning can keep pace

You're switching to an unrelated task that shares no context

Open a fresh window and re-ground it from your config and memory.

Levers You Can Set



cleanupPeriodDays

Controls how long session data is retained on disk before cleanup, defaulting to thirty days.



File checkpointing

When enabled, lets you rewind file changes to an earlier point in the session.



Auto memory toggle

Turns Claude's own cross-session memory on or off, so learnings persist only when you want them to.



On-demand compaction

You can trigger a compaction yourself at a natural break instead of waiting for the window to fill.

Re-Grounding From Config




CLAUDE.md

Your written instructions. They load into a fresh session automatically, restoring durable rules the moment you start.



Auto memory

Claude's own learnings on disk. Only the top of the MEMORY.md index loads at start, with topic files pulled as needed.



settings.json

Your permissions, hooks, and environment. It reapplies on a fresh session so the harness behaves the same way every time.

Handing Off Cleanly

Before you reset, carry forward only what the next step actually needs.

Write a short summary
of decisions and open threads

Save durable facts
to CLAUDE.md or memory, not the chat

Drop the raw history
once its takeaways are recorded

Handoff Summary

Notes for next session

Goal

Build a customer support triage assistant

Decisions

- Use RAG over docs
- Classify intent first
- Escalate high-risk cases to human

Open Threads

- Add KB for returns
- Define escalation thresholds
- Evaluate tone settings

Key Context

- Product docs (v1.3)
- Support team handoff flow
- Next review Aug 28

Store in CLAUDE.md
Durable memory for the next session

Choosing the Right Reset



Compact to summarize history and keep going



Clear to empty the window without leaving the session



Start fresh when the session drifts or switches tasks



Re-ground every reset from CLAUDE.md, memory, and settings


Installing and Configuring Plugins

Plugins package new commands, skills, and integrations into one installable unit you can layer onto Claude Code.



plugin.json

```
{
  "name": "code-linter",
  "version": "1.2.0",
  "description": "Static code
   analysis and style checks",
  "author": {
    "name": "devtools",
    "email": "team@devtools.dev"
  },
  "keywords": ["lint", "format"]
}
```



What a Plugin Is



Plugin

A self-contained directory that extends Claude Code with new capabilities, packaged so you install it as one unit.



Manifest

The `.claude-plugin/plugin.json` file that identifies the plugin and declares what it provides.



Marketplace

A catalog that lists available plugins, so you can browse and install from a trusted source.

What Plugins Add

A single plugin can bundle several kinds of capability at once.


Slash commands and skills
that add new workflows

Subagents and hooks
that run automatically

MCP servers, LSP servers, and background monitors




Marketplaces vs Plugins



Marketplace

A marketplace is the catalog you register first. Adding one lets Claude Code see the plugins it offers, but it installs nothing on its own.



Plugin

A plugin is an individual capability you install from a registered marketplace. Installing is the second, separate step that actually adds the plugin.

How Installing Works

Getting a plugin in place is a two-step flow you run from the plugin commands.



1
Add Marketplace



2
Install Plugin



First, add the marketplace so Claude Code can see its catalog



Then install the plugin by name, scoped to that marketplace



Marketplace = A source of plugins with a public catalog



Plugin = A unit with tools, prompts, and metadata



Install = Claude Code downloads and makes it available



Scoped install = Bound to the selected marketplace

The official marketplace is already available, so you only add community ones yourself.

Managing Installed Plugins



list

Shows every installed plugin and whether it is enabled or disabled, with flags to filter by state.



enable and disable

Turn a plugin on or off in place. Disabling keeps it installed, so you can switch it back on later.



uninstall

Removes a plugin and its files completely, the clean choice when you no longer need that capability.

Inside the Plugin Manager

Running the plugin command with no arguments opens an interactive manager with four tabs.

Discover, for browsing plugins you could add

Installed, for what you already have and its state

Marketplaces, for the catalogs you have registered

Errors, for plugins that failed to load



Configuring and Reloading



Install Scope

When you install, you choose a scope, deciding whether the plugin is just for you or for the whole project.



Per-Plugin Config

Some plugins take configuration values that tune their behavior, stored so the settings persist across sessions.




reload-plugins

Applies enable, disable, and install changes to the running session, so you don't have to restart Claude Code.

Plugins vs Rules vs Permissions

Three kinds of configuration often get confused, so keep their jobs separate.



Plugins add new capabilities, the commands and tools themselves

CLAUDE.md gives natural-language instructions Claude reads as context

settings.json sets permissions and other machine-readable options

Same project, three layers, each doing a different job.

Installing Plugins in Practice



A plugin is a self-contained directory, usually with a plugin.json manifest



Add a marketplace first, then install plugins from it



Enable, disable, and uninstall control each plugin's state




reload-plugins applies changes without a restart




Plugins, CLAUDE.md, and settings.json each play a different role

Sharing Plugins Across a Team

A plugin that works on your machine does no good if your teammates don't have it too.








Four Install Scopes



User

Your default scope. The plugin is available in all of your own projects, but only for you.



Project

Shared with every collaborator. Written to the project settings file so the whole team gets it.



Local

Just you, just this repository. Handy for a plugin you want here without affecting other projects.



Managed

Installed by administrators through managed settings. You cannot modify or remove it yourself.


Sharing Through Version Control

The project scope is how a team stays in sync on plugins.

It writes plugin settings into the project settings file

That file is committed to source control, so it travels with the repo

When teammates pull, they get the same marketplaces and plugins



Personal vs Shared Scopes



Personal (User, Local)

User and Local scopes stay with you alone. They never touch source control, so teammates see nothing, and each person manages their own setup.



Shared (Project, Managed)

Project and Managed scopes reach the whole team. Project travels through the repo, while Managed is set centrally by administrators and locked.

Settings That Track Plugins




enabledPlugins

Records which plugins are turned on in this scope, so the right ones activate when the project loads.



extraKnownMarketplaces

Lists the marketplaces a project trusts beyond the official one, so teammates can install the same plugins.




pluginConfigs

Holds per-plugin configuration values, keeping each plugin's options consistent for everyone sharing the file.

Auditing What's Installed

Before trusting a project's setup, take stock of what is actually there.



Run the list command
to see every plugin and its state

Filter by enabled or disabled
to spot what is active

Check each plugin's scope
to see who it affects

Review what each one is permitted to do
before relying on it

Trust and Safety



Arbitrary Code

Plugins run with your full privileges, so a bad one can do anything you can do.



Trusted Sources

Install only from marketplaces and authors you trust, the same care you give any dependency.



Org Guardrails

Administrators can restrict which marketplaces are allowed through managed settings across the whole organization.


Removing Plugins Cleanly

When a capability is no longer needed, remove it without leaving loose ends.

Disable a plugin
to pause it while keeping it installed

Uninstall
to delete a plugin and its files for good

Removing a marketplace
also uninstalls every plugin that came from it



Keeping a Team in Sync



Commit the Config

Put the project settings file in source control so the plugin setup ships with the code.



Document the Marketplace

Note any extra marketplaces the project trusts, so teammates know where its plugins come from.



Re-audit on Pull

After pulling changes, review new or updated plugins before running them, since they execute with your privileges.

Plugins Across a Team



User and Local are personal; **Project** and **Managed** are shared



Commit the project settings file to share plugins via the repo



Audit each plugin's scope and permissions




Plugins run with your privileges, so install from trusted sources




Removing a marketplace uninstalls its plugins


Writing Effective CLAUDE.md Rules

A CLAUDE.md file holds developer-authored rules that load into context at the start of every session.





Three Kinds of Session Knowledge




CLAUDE.md

Developer-authored rules loaded into context at session start. They are static, you write them, and they apply to every turn.



Agent memory

Durable state the agent itself writes and updates. It survives context compaction and session boundaries.



Context window

The ephemeral working space for the current session. It truncates, so nothing there persists on its own.

Rules, Not Enforcement

Claude treats CLAUDE.md as context to consider, not configuration it is forced to obey.




It is guidance
the model reads,
not a hard constraint



A rule can be missed
when the context
gets crowded




To truly block an action,
use a PreToolUse hook



Write rules to steer behavior, and use hooks when you need enforcement.

What Belongs in CLAUDE.md




Project structure

Where things live, key directories, and how the codebase is organized so Claude navigates fast.



Conventions

Coding style, naming, and patterns the team follows, stated plainly so output matches your norms.




Commands

The exact build, test, and lint commands, written verbatim so Claude can copy and run them.

It Costs Context, Not Free Memory

Every line in CLAUDE.md loads into the context window, so treat the space as a budget.




The whole file loads in full, regardless of length

A bloated file crowds out room for actual work

Aim to keep it under a couple hundred lines

Scoped Rules vs Verbose Prose



Scoped rules

Short, specific, and testable. Structure, conventions, and commands stated as clear directives the model can act on every turn without guessing.



Verbose prose

Long paragraphs of background and rationale. They burn context, bury the one instruction that mattered, and make it harder for Claude to follow.


Commit It for the Whole Team

A project CLAUDE.md lives at the repo root and travels through source control.

Commit it so every teammate inherits the same conventions

New contributors get your build commands on day one

Behavior stays consistent across everyone's sessions



How CLAUDE.md Reaches Claude



Loaded at start

It is injected at the beginning of every conversation, so the rules are present before your first request.



A user message

It arrives as a user or project message alongside the system prompt, not baked into the system prompt itself.




Loaded in full

Unlike capped memory files, the entire CLAUDE.md loads regardless of how long it is.

Write Rules Claude Will Follow

Good rules read like directives, not documentation. Make each one easy to act on.

Example: Support Ticket Triage Agent



Tools (config.json)

```
{
  "tools": [
    {
      "name": "refund_ticket",
      "description": "Issue a refund for an eligible order.",
      "endpoint": "https://api.example.com/v1/refunds",
      "method": "POST",
      "auth": "Bearer {{API_KEY}}"
    },
    {
      "name": "search_docs", "description": "Find answers in docs."
} ]
}
```

Sample Ticket

```
{
  "id": "TCK-48217",
  "customer": "jane.doe",
  "subject": "Refund
  request",
  "channel": "web",
  "priority": "medium",
  "created_at": "2025-05-22
  14:37:18Z"
}
```

Use imperative, scoped statements over background prose

Tell Claude exactly what to do, in what scope, and with what limits. Remove history, rationale, and anything not required to act.

Put commands verbatim so they are copy-ready

Include exact commands, endpoints, and payloads. Make them runnable as-is without reformatting.

Trim anything that does not change behavior

Cut examples, filler, alternatives, and explanations that do not affect Claude's decisions or actions.

Rules Worth Loading



It holds structure, conventions, and commands



It is context to consider, not enforced configuration



Its content counts against the context window



Commit the project file so the team shares it


The CLAUDE.md Precedence Hierarchy

CLAUDE.md files exist at several scopes, from a machine-wide managed policy down to a personal local file.

Precedence (Highest -> Lowest)

1. **Managed Policy**
   Machine-wide
2. **Organization**
   org/CLAUDE.md
3. **Project**
   .claude/CLAUDE.md
4. **Directory**
   CLAUDE.md
5. **Local File**
   Closest CLAUDE.md

How Precedence Works



Definitions here apply everywhere and **cannot** be overridden.


Inherits above. Can **override** or extend for the organization.

Inherits above. Can **override** or extend for this project.

Inherits above. Can **override** or extend for this directory.

Inherits above. Can **override** or extend for this file.

Four Places Rules Live



Managed policy

Deployed machine-wide by administrators. It loads first and cannot be excluded by any user.



User

Your personal file in the home config directory. It applies across all of your projects.



Project

Committed at the repo root or project config folder. It is shared with the whole team.



Local

A personal, gitignored file for one project. It stays with you and is never committed.

Load Order, Broad to Specific

Claude walks up the directory tree from where you launched it, gathering every CLAUDE.md it finds.

Files are concatenated, not overriding each other


All discovered CLAUDE.md files contribute to the final context.

They order from the filesystem root downward


Broader, higher-level files are read before more specific ones.

The most specific file is read last

Specific instructions win naturally because they come later.



Three Layering Facts



Concatenation

Every discovered file is stacked together into context. No file erases another, they combine.



Root-down order

Files load from the filesystem root down to your working directory, so the closest one lands last.



Composition


The design intent is layering, not strict override. If rules truly conflict, Claude may pick either one.

Project Level vs User Level



User level

Your home-directory file, the personal baseline that follows you across every project. Broad defaults you want in every repository live here.




Project level

The repo file, read after the user file, so it tends to win when the two disagree, though nothing enforces that. Team conventions for this specific codebase live here.

Subdirectory Files Load on Demand

Not every CLAUDE.md loads at launch. Files below your working directory wait until they are needed.




A nested file loads when Claude reads a file in that folder

It is not injected at session start

This keeps deep, folder-specific rules out of the way

How Imports Work



Import syntax

An at-path reference expands another file into context at launch, resolved relative to the importing file.



Four-hop limit

Imports can chain, but the recursion stops at a maximum depth of four hops.



Still costs context

Imported files load into context too, so imports organize your rules, they do not save tokens.


Managed Policy Can't Be Removed

A managed policy file sits above the whole hierarchy and no user can remove it.

It loads before
the user and project files


Admins can embed
its rules through a managed setting

Exclusion globs can
drop ancestor files but never this one



Design for Composition

Because files layer instead of hard-overriding, the safest design avoids conflicts altogether.



Put broad defaults at the user level

Set organization-wide preferences, model choices, and safety guardrails once. Applies to all projects unless overridden.

Put team rules in the committed project file

Capture consistent conventions, tooling, and standards in the project file. Shared by everyone on the team.

Keep folder-specific rules in subdirectory files

Add focused rules for code, tests, docs, or scripts where they matter. Local overrides stay scoped and clear.

Reading Order Is Precedence



Managed policy loads first and cannot be excluded



Files concatenate, the most specific reads last



Project usually wins over user since it reads later, so design conflicts out



Subdirectory files and imports load on their own terms

settings.json Permissions and Hooks

settings.json is the machine-readable control layer for Claude Code.



Three Things to Configure



Permissions

Rules that allow, deny, or ask before Claude runs a given tool or command, so risky actions are gated deterministically.



Hooks

Deterministic scripts registered here that fire at fixed lifecycle events, running outside the model to enforce, log, or automate.



Environment

Variables and model choice set through config, so the same values apply every session without being hardcoded in your app.

Three Permission Rules



allow

Lets a matching tool call run automatically, with no prompt, because you have already trusted that action.



deny

Blocks a matching tool call outright, so a dangerous or unwanted action never executes at all.



ask

Pauses and prompts you to approve or reject the call, keeping a human in the loop for sensitive actions.

Registering a Hook

A hook wires a deterministic script to a moment in the agent's lifecycle.

You declare it in settings.json, not in prose


Hooks live in your project config, versioned and reviewable.

It names the event that should trigger it

You choose the lifecycle moment that should fire the hook.

It points to the command that runs at that event


The command executes with context and returns output to the agent.



Because it lives in config, it fires the same way every time, regardless of what the model decides.

Five Lifecycle Events

Hooks can fire at several lifecycle points, and these five are common places to enforce or log.



PreToolUse, before a tool call runs

PostToolUse, after a tool call finishes

Notification, when Claude surfaces a message

Stop, when a response completes

SessionStart, when a new session begins

PreToolUse vs PostToolUse



PreToolUse

Fires before a pending tool call executes, so it can deny or ask on a dangerous action and actually stop it. This is where guardrails belong.



PostToolUse

Fires after a tool call has finished, so it can log or react, but it cannot block something that has already run.

Four permissionDecision Values



allow

Approves the pending tool call and lets it run with no prompt at all.




deny

Blocks the pending call outright, so it never executes at all.



ask

Hands the decision back to you to approve or reject the pending call.



defer

Falls back to your normal permission rules instead of forcing an outcome here.

Environment and Model Choice

Config also handles values you'd otherwise hardcode, keeping them in one shared place.




Environment variables your tools and hooks can read

Centralize keys, endpoints, toggles, and feature flags in config.




A default model and a fallback for the session

Set the primary model to try first and a backup to use on failure.



Effort level and other harness options


Tune reasoning effort, timeouts, retries, and safety behaviors.



Set once in config, these apply consistently instead of being scattered through your code.

Where Each Change Belongs

Two control layers get confused, so keep their jobs separate.



settings.json holds machine-readable config, permissions, hooks, and env

CLAUDE.md holds natural-language instructions Claude reads as context

Permissions and hooks belong in settings.json, never in prose

Most settings.json keys reload live, though model and output style need a restart.

The settings.json Control Layer



Permissions gate tools with allow, deny, and ask



Hooks fire deterministic scripts at lifecycle events



PreToolUse is where guardrails belong, before an action runs



Environment variables and model choice come from config



Config and permissions live here; instructions live in CLAUDE.md

Layering User, Project, and Local Config

The same setting can be defined in more than one place, so config is layered by scope.

Lowest Precedence



User Config

Global defaults across all projects



`~/.claude/settings.json`

Personal



Project Config

Team or project specific settings



`.claude/settings.json`

Committed

Highest Precedence



Local Config

Developer machine overrides



`.claude/settings.local.json`

Gitignored



Effective Configuration

Final value used at runtime

Four Config Layers

User — Your personal settings at ~/.claude/settings.json, applied across all of your own projects.

Project — Committed team settings at .claude/settings.json, shared with everyone through source control.

Local — Personal, repo-specific settings at .claude/settings.local.json, gitignored so they never get committed.


Managed — Policy settings deployed by IT, applied machine-wide and not overridable by users.

Where Each File Lives



User settings

The file at ~/.claude/settings.json. It's personal to you and follows you into every project on your machine.



Project settings

The file at .claude/settings.json. It's committed to git, so the whole team inherits the same configuration.



Local settings

The file at .claude/settings.local.json. It's auto-gitignored, so your personal overrides stay on your machine.


Precedence, Highest to Lowest

When a setting is defined in more than one layer, precedence decides which value actually applies.

Managed policy wins over everything and can't be overridden

Command-line arguments come next, per the docs

Then local, then project, then user settings



So the more specific and higher-priority the layer, the more it takes precedence over the broader ones below it.

Committed vs Gitignored



Project settings (committed)

The .claude/settings.json file is committed to git, so it travels with the repo and every teammate inherits the same permissions, hooks, and config.




Local settings (gitignored)

The .claude/settings.local.json file is auto-gitignored, so it stays on your machine and never lands in the shared repo, which makes it the right home for personal overrides and anything you don't want teammates to inherit.

Why the Split Matters

The committed-versus-personal split isn't just tidiness, it changes how trust and sharing work.



Shared project rules travel to the whole team, so they need workspace trust

Personal local rules are yours alone, so they need no trust prompt

Secrets and machine-specific values belong in local, not the committed file

Diagnosing Which Layer Wins



Check every layer

List where the setting is defined, from user all the way up to managed policy.



Apply precedence

The highest-priority layer wins, so a local value beats a project value beats a user value.



Suspect managed first

If a value won't change no matter what you edit, a managed policy is likely overriding it.

Reading Precedence in Practice

Picture the same permission defined in more than one layer, and watch who wins.



A value in local overrides the same value in project



A value in project overrides the same value in user



A managed policy overrides all of them, every time



When a setting surprises you, walk the layers from the top and the conflict explains itself.

settings.local.json Discipline



Commit shared config

Put team-wide permissions and hooks in .claude/settings.json so everyone works from the same rules.



Gitignore the local file

Leave .claude/settings.local.json out of the repo. It's auto-gitignored by default, so personal overrides stay yours.



Keep secrets out of git

Store machine-specific values and anything sensitive in the local file, never in the committed shared one.

How Config Layers Resolve



User, project, local, and managed layers stack by scope



Managed wins over all; local beats project beats user



Project settings.json is committed; settings.local.json is gitignored



Keep shared rules in project, personal or sensitive values in local



To debug, find every layer defining the setting and apply precedence

Versioning Prompts and Config

A prompt is code, and a change to it can regress behavior just like a code change.

retail-support-bot

- prompts/
  - system.md — v1.2.0
  - routing.md — v1.3.1
  - refusal.md — v1.0.2
- config/
  - tools.yaml — v2.1.0
  - model.yaml — v1.4.3
- .env.example
- README.md

prompts/system.md — v1.2.0

```
1  You are a helpful retail support assistant.
2  Follow these guidelines:
3  - Be concise and friendly.
4  - Use the available tools when needed.
5  - Never make up information.
6  - Escalate when the issue is outside policy.
7
8  If unsure, ask for more details.
```

Commit History

9f3b1a2 today dev-team
Tune escalation guidance and add examples
prompts/system.md v1.2.0
prompts/routing.md v1.3.1

7c8d4e1 2 days ago dev-team
Improve routing rules for order issues
prompts/routing.md v1.3.0
config/tools.yaml v2.1.0

4a1d9c7 5 days ago dev-team
Add refund tool and update tool config
config/tools.yaml v2.0.0
prompts/system.md v1.1.0

d2b7e93 1 week ago dev-team
Clarify refusal behavior and boundaries
prompts/refusal.md v1.0.2

a0c3b11 2 weeks ago dev-team
Initial prompt and configuration
prompts/system.md v1.0.0
config/model.yaml v1.0.0

Three Terms for Versioning



Prompt Versioning

Treating prompts as versioned artifacts, tracked in source control and tied to a model version, so a change is reviewable and reversible.



Regression Eval Set

A frozen set of inputs and expected outputs you run each version against, catching a regression before your users do.



anthropic-version Header

A required header pinning API request and response behavior to a dated version, so the contract can't shift under you.

Treat Prompts Like Code

A prompt shapes behavior, so a prompt change deserves the same rigor as a code change.



Keep every system prompt in source control, not pasted ad hoc



Review prompt edits the way you review a pull request



Tie each prompt version to the model ID it was tuned for

prompts/support_agent.md +7 -6

```
@@ -21,12 +21,13 @@
21     You are a support agent for Acme.
22     Be helpful, concise, and accurate.
23 -   Do not make up information.
24 -   If unsure, ask one clarifying question.
25 -   Use the knowledge base when available.
26 -   End replies with a brief summary.
27     ---
28 +   If information is missing, ask up to two
29 +   clarifying questions before answering.
30 +   Prefer citing the knowledge base with a
31     reference ID.
32 +   Keep answers under 120 words.
```


Edited-in-production prompts are the ones that regress silently.

What to Version Together



The prompt text

Every system prompt and instruction block, committed as a file so each edit shows up in history.



The model ID

The exact pinned ID the prompt was tuned against, versioned right beside the prompt it pairs with.



The config

The settings.json, permissions, and hooks that shape behavior, committed so the whole setup is reproducible.

The anthropic-version Header

The API gives you one concrete pin for request behavior, the anthropic-version header.

```
POST https://api.anthropic.com/v1/messages

HEADERS
Host:              api.anthropic.com
Content-Type:      application/json
x-api-key:         <redacted>
anthropic-version: 2023-06-01

BODY
{
  "model": "claude-opus-5",
  "max_tokens": 1024,
  "messages": [
    { "role": "user", "content": "What's in the report?" }
  ]
}
```



It pins request and response behavior to a dated API version




It's required, and the SDKs set it for you automatically



Within a version, Anthropic only adds, never breaks fields


Pin the version explicitly so upgrades are a choice, not a surprise.

Ad Hoc Edit vs. Versioned Change



Ad hoc edit

Someone tweaks the live prompt to fix one case. There's no record, no review, and no way to reproduce yesterday's behavior when something breaks.



Versioned change

The edit lands as a reviewed commit tied to a model ID. History shows what changed and when, so you can roll back to any known-good version.


Test Before You Promote

Never promote a new model or prompt version straight to production.

Run the candidate against your frozen eval set first

Compare its outputs to the current version's known results

Promote only when the new version matches or beats it




Three Ways Versions Get Tracked



Source control

Your own commits are the primary record. A prompt, its model ID, and config all live in git, so history is the version log.



SemVer in plugin.json

A Claude Code plugin carries a version field using major, minor, patch, so consumers can pin or track it deliberately.




Commit SHA fallback

When a plugin omits its version, the git commit SHA becomes the version, so every commit counts as a new one.

Roll Back When Behavior Regresses

When a release changes behavior for the worse, versioning makes recovery easy.



Repoint the pin to the last known-good model ID

Move the current pin back to the last stable version.

Restore the matching prompt version from source control

Check out the prompt version that matches the model.

Confirm the rollback against the same evals that caught it

Re-run the evaluation suite to verify behavior is restored.

Versioning as Maintenance Discipline



Treat prompts as versioned artifacts, tracked in source control



Pin the anthropic-version header to lock API behavior



Version the prompt, its model ID, and config together




Test every new version against a frozen eval set first




Roll back to a known-good version when behavior regresses

Resolving Plugin Dependencies

Plugins rarely stand alone. Most rely on other plugins to work,
and Claude Code lets one declare exactly what it needs.





How Plugins Declare Needs



Dependency

Another plugin that this one relies on to function. Without it present and enabled, the plugin's features break.



dependencies array

A list in the plugin manifest naming what it needs. Entries are a bare name or a versioned object.



Auto-install

Installing a plugin resolves its array and pulls in every dependency for you, listing each addition.

Declaring a Dependency

An entry in the dependencies array can be simple or precise, depending on how tightly you pin it.



A bare plugin name string
tracks whatever the marketplace currently provides



An object adds a version range
to constrain which release resolves



An object can also name a
different marketplace to source from

Blocked by default until the root marketplace allowlists the target in allowCrossMarketplaceDependenciesOn

```
{
    "name": "weather-dashboard",
    "version": "1.0.0",
    "dependencies": [
        "acme-maps",
        {
            "name": "acme-charts",
            "version": "^2.3.0"
        },
        {
            "name": "theme-light",
            "version": "~1.4.0",
            "marketplace": "acme-shared"
        }
    ]
}
```

Bare Name vs Pinned Version



Bare Name String


You list just the plugin name. It tracks whatever version the marketplace currently offers, so you always get the latest available. Simple, but the resolved version can shift under you.



Pinned Version Object


You wrap the name with a semver range like tilde two point one. Claude Code fetches the highest tagged version that satisfies it, giving you a predictable, reproducible resolve.

Semver Range Examples



Tilde ~2.1.0

Allows patch updates within the two point one line. Picks the newest two point one point x release available.



Caret ^2.0

Allows minor and patch updates below the next major. Stays on version two, moving up as features ship.




Comparator >=1.4

Accepts any version at or above one point four. Broadest of the three, with the least protection from breaking changes.

Auto-Install and Transitive Enable

Dependencies don't just install together, they turn on together too.



Enabling a plugin also enables its dependencies at the same scope

This happens transitively, down the whole chain of needs

A dependency pulled in this way is marked enabled even if its own manifest defaults to off


When Disable Is Blocked

You can't always turn a plugin off on demand. The dependency graph protects what's still in use.

Disabling is blocked if another enabled plugin still depends on it


Claude Code prints the chained command to disable the dependents first

Once nothing depends on it, the disable goes through cleanly




This keeps you from silently breaking a plugin that something else still needs.

When Constraints Collide




Constraint intersection

When several plugins constrain the same dependency, Claude Code intersects their ranges and picks the highest version satisfying all of them.



range-conflict

The error raised when those ranges can't be reconciled. The install fails and your existing setup is preserved.




Highest satisfying version

Within any single range, resolution always fetches the newest tagged release that still fits the constraint.

Cleaning Up Orphans

Removing a plugin doesn't remove what it dragged in. Auto-installed dependencies linger.



Those leftovers are orphans, kept in case something else still needs them


Run plugin prune to sweep orphaned auto-installed dependencies away

Prune never touches plugins you installed directly, only the auto-pulled extras

Dependencies That Resolve



Plugins declare needs in a dependencies array, bare or version-pinned



Install and enable both cascade to dependencies automatically




Disable is blocked while an enabled plugin still needs the dependency




Prune clears orphaned auto-installed dependencies safely

Sharing Dependencies Across a Team

A plugin that works on your machine can break for a teammate when its dependencies aren't shared.






Plugins Are Not Self-Contained

Treating a plugin as a standalone box is the root of most team breakage.

A plugin is really the tip of a dependency graph

It needs other plugins present, enabled, and version-compatible

Share the plugin alone and a teammate's install breaks




How Versions Resolve




Git-tag resolution

Version ranges resolve against repo tags named plugin-name, two dashes, v, then the version, like logger--v2.1.0.



plugin tag --push

The command a plugin author runs to publish the version tags that dependency resolution reads.




no-matching-tag

The error when no published tag satisfies a range. The dependent plugin is disabled rather than mis-resolved.

Commit Dependencies to Version Control

Reproducibility comes from committing the right files, not from documenting steps.



The plugin manifest's dependencies array
declares what is needed

Project settings
record which plugins are enabled for the team

A teammate's clone
resolves the same declared set every time

Dependency Error Codes




dependency-unsatisfied

A required dependency is missing or disabled, so the plugin cannot load its features.



dependency-version-unsatisfied

The dependency is installed, but its version falls outside the declared range.



no-matching-tag


No published git tag satisfies the range, so the dependent plugin stays disabled.



range-conflict

Two plugins demand versions that can't be reconciled, so the install fails safely.

Same vs Cross-Marketplace



Same Marketplace

A plugin and its dependency in the same catalog resolve automatically. This is the default, frictionless path and the common case for a shared team setup.



Cross-Marketplace

Depending on a plugin in a different catalog is blocked by default. The root marketplace has to allowlist the target, or the install fails with a cross-marketplace error.

Diagnosing a Broken Plugin

Diagnose from the error code, not by reinstalling and hoping.



Run plugin list with the json flag and read the errors field



The code tells you missing, wrong-version, untagged, or conflict



Each code maps to one targeted fix

```
$ claude plugin list --json
{
  "ok": false,
  "count": 4,
  "errors": [
    { "code": "dependency-unsatisfied",
      "id": "weather" },
    { "code": "dependency-version-unsatisfied",
      "id": "payments" },
    { "code": "no-matching-tag", "id": "analytics" },
    { "code": "range-conflict", "id": "auth" }
  ]
}
```

Keeping Manifests Honest



defaultEnabled override

A dependency needed by an active plugin is enabled even if its own manifest sets defaultEnabled to false.



plugin prune

Removes orphaned auto-installed dependencies that nothing points at, never plugins you installed directly.



Cross-marketplace allowlist

A marketplace-file field naming which outside plugins may be depended on, opting into an otherwise-blocked catalog.

Keeping Dependencies Current

Dependency work is ongoing maintenance, not a one-time setup.



Example update

```
{
  "plugin": "payments-gateway",
  "from": "^2.4.0",
  "to": "^2.5.1",
  "changes": ["fix: retry logic", "chore: deps"],
  "advisory": "GHSA-7c8m-2w9x-v4j2"
}
```

Adding a plugin means committing its dependency declarations

Bumping a version means updating the range and re-tagging

Retiring a plugin means pruning the orphans it leaves

Consistent Environments for Everyone



Version control carries declarations, enabled plugins, and version tags



Git tags in the plugin-name--vX pattern make resolution reproducible



Cross-marketplace dependencies stay blocked until explicitly allowlisted



Error codes pinpoint missing, wrong-version, untagged, or conflicting deps