

Tool Descriptions as the Routing Contract

When Claude picks a tool, it reads your prose, not your mind.
The description you write is the signal that decides which tool fires.





Three Definition Fields




name

A unique identifier Claude uses to call the tool. It matches a strict pattern of letters, digits, underscores, and hyphens.



description

Plaintext prose stating what the tool does, when to use it, and how it behaves. This is the primary routing signal.



input_schema

A JSON Schema object declaring the parameters Claude may pass, their types, and which fields are required.


The Description Is the Router

Claude decides when to call a tool from the user's request and the tool's description.

The description is by far the most important factor in tool performance


Claude reads it to judge whether this tool fits the request

Terse labels leave the model guessing at intent



Precise prose is what turns a request into the right call.

Name vs. Description



Name

The identifier your code and the API use to invoke and match the tool at execution time. It does little routing work on its own.



Description

The natural-language routing signal Claude reasons over to choose among tools. Improving it is the first fix for wrong tool choices.

Four Things a Description Covers



What it does

State the tool's job in plain language so Claude knows the capability it offers.



When to use it

Name the situations and requests this tool is the right choice for.



When not to use it

Call out cases where a different tool fits better, preventing misroutes.



Caveats and limits

Note parameter meanings, side effects, and boundaries the model needs to respect.

Why Schema Alone Falls Short

A schema tells Claude what is structurally valid, but not when a call makes sense.

Example: Weather Lookup Tool

object

location	string	required
units	string	optional
days	integer	optional
include_alerts	boolean	optional



What this schema says:

These fields exist, their types, and which are optional.

What this schema doesn't say:

When to include units vs. days, or when alerts actually matter.

Schemas can't express usage patterns or intent

They define structure, not the conditions under which a tool should be called.

They don't say which optional fields to include when

Schemas list what's possible, but not what's appropriate in a given situation.

Only the description carries the when and why

The natural language description guides judgment, trade-offs, and priorities.

So the schema constrains the shape while the description drives the choice.

Write It Like an Onboarding Doc

Treat the description as onboarding notes for a new hire who has never seen the tool.

Aim for three to four sentences, more if the tool is complex

Give enough detail for someone new to build confidence and use the tool correctly without guesswork.

Explain what each parameter means and how it shapes behavior

Connect inputs to outcomes so the reader understands why a setting exists and when to change it.

Spell out edge cases instead of assuming context

Highlight limits, failures, and unusual scenarios so the reader can act safely in the real world.

Detailed prose beats a clever name every time.

Example Tool: customer_lookup

Find a customer by email and return profile details.



Parameters

email (string, required)	Customer email address to search.
include_history (bool, default: false)	Include order history when true.
limit (integer, default: 1)	Max number of matches to return.
timeout_ms (integer, default: 5000)	Request timeout in milliseconds.
region (string, default: "us-east-1")	Data region for the lookup.

Vague vs. Precise Description



Vague

A tool named get_data described only as data tool invites misrouting. Claude can't tell what data it returns, from where, or when to use it.



Precise

search_orders, described as retrieving a customer's orders for support questions, routes cleanly and fills the arguments correctly.

Fixing a Tool Claude Skips

When Claude ignores or misuses a tool, the description is the first thing to fix.



A skipped tool usually has a thin description

Vague descriptions give the model little reason to call the tool.



Add intent, conditions, and concrete examples of when it applies

Specific guidance helps Claude recognize the right moments to use it.



Rewrite before you touch temperature or the model

A stronger description fixes the root cause more reliably than tuning.

Sharper prose recovers more bad tool choices than any other change.

Descriptions Do the Routing



The description is the primary signal Claude selects on



The name identifies the tool for execution, not routing



Schemas define valid shape, not when to call




Write three to four sentences of real intent




Vague descriptions are the top cause of misrouting

JSON Schemas for Tool Inputs

A tool's input_schema is the contract for its arguments. It tells Claude which fields exist, their types, and which ones are required.






The Schema's Three Jobs



Declare the fields

The schema lists every parameter the tool accepts, giving each a name Claude fills when it calls the tool.



Type each field

Every parameter gets a type, string, integer, boolean, array, or object, so the model supplies the right shape.



Mark required fields

The required list names parameters the model can't omit, while everything else stays optional.

Arguments Come Back as JSON

When Claude calls a tool, its arguments arrive as a JSON object that matches your schema.

You parse a structured object, not free-form text


Claude returns arguments as JSON, so your code can parse and validate them reliably.

Each key maps to a field you declared in the schema

The keys in the JSON line up exactly with the fields and types in your tool schema.


The schema is what makes the output predictable

A well-defined schema constrains the model, reducing surprises and improving reliability.




That's why typed fields matter. They shape what you get back.

Schema Building Blocks



Types

Declare string, integer, boolean, array, or object so each argument arrives in the shape your code expects.



Enums


List the allowed values for a field so the model can only pick from a fixed, valid set.



Descriptions

Add a short description to each property, telling Claude what the field means and how to fill it.

Required vs. Optional



Required

Reserve the required list for fields with no safe default, the values the tool genuinely can't run without, such as a record ID.



Optional

Everything else stays optional. Over-marking required fields forces Claude to stop and ask the user instead of proceeding with the call.

Enums Pin Down Categories

When a field has a fixed set of valid values, an enum is far better than an open string.





An open string invites typos and invented values

Anything goes - misspellings, duplicates, and inconsistent labels slip through.



An enum limits the model to values you actually handle

The model can only choose from the list, eliminating invalid or unsupported values.



Categorical inputs like status or priority are ideal enums

Finite categories map cleanly to enums, improving reliability and downstream logic.

Constrain the choice and you head off a class of bad arguments.

Three Field-Level Choices



Narrow the type

Prefer the tightest type that fits. An integer beats a string when the value is always a number.



Constrain with enums

Replace free-form categories with an enum so only handled values reach your code.



Describe each property

A per-field description tells Claude what the value means, cutting ambiguous or malformed arguments.

Strict Makes Inputs Conform

Setting strict true on a tool guarantees the arguments Claude generates match your schema exactly.

It uses grammar-constrained sampling during generation


Claude's decoder is constrained by your JSON Schema, so only valid tokens are ever sampled.

Missing parameters and type mismatches are eliminated

Outputs that violate the schema cannot be produced, preventing incomplete or invalid tool calls.


Pair it with forced tool use for a guaranteed valid call

Claude will always return a tool call that conforms to your schema- no free-form text, no guesses.




Strict turns the schema from a hope into a hard guarantee.

Structurally Valid vs. Correct



Structurally valid

The arguments match the schema, right types and every required field present. That's what a good schema and strict guarantee for you.



Actually correct

A schema-valid call can still fail at runtime, from a missing record or a bad state. Structural validity is never execution success.

Design the Schema to Constrain



Arguments come back as a JSON object you parse



Use narrow types and enums over open strings



Require only fields with no safe default



Strict grammar - enforces schema conformance




Schema-valid still isn't the same as correct at runtime

Tool Definitions Claude Calls Well

You've written the name, description, and schema. Now they work inside the tool-use loop where Claude calls and your code responds. This lesson covers the round trip, the four tool_choice values, Anthropic's client tools, and the mistakes that make Claude misfire.





Three Blocks in the Loop



tool_use

The block Claude returns when it calls a tool, carrying an id, the tool name, and an input object.



tool_result

The block your code returns after running the tool, handing the output back for Claude to reason over.



tool_use_id

The id that links a tool_result to the tool_use it answers, so Claude matches output to the right call.

The Round Trip in Four Steps


A tool call is a round trip between Claude and your code, in four steps.

You send the request along with your tool definitions

Claude returns `stop_reason` `tool_use` with the call and its input

Your code runs the tool and returns a `tool_result`

Claude reads the result and answers the user



Returning Results the Right Way

The tool_result block is how you hand an answer back to Claude.

Match it to the call with the same tool_use_id

Use the exact tool_use_id from Claude's tool_use block so results are linked to the right call.

Put every result inside a single user message

Return one user message that contains all tool_result blocks together.

Include results for every tool_use block Claude sent

Provide a tool_result for each tool_use block so nothing is left unanswered.

Claude sends tool requests

```
id: call_1
name: get_weather
input: {"location": "Tokyo"}
```

```
id: call_2
name: get_time
input: {"timezone": "Asia/Tokyo"}
```

You return one user message


```
content: [
  tool_result
  tool_use_id: call_1
  content: {"temp_c": 28, "condition": "Sunny"}
  tool_result
  tool_use_id: call_2
  content: {"time": "14:37", "timezone": "Asia/Tokyo"}
]
```

Claude continues

Receives results and continues reasoning or completes the task.


Skip one and the API rejects the turn, so account for all of them.

Parallel Tool Calls




Multiple at once

Claude can emit several independent tool_use blocks in a single message whenever the calls do not depend on each other.



One combined reply

Return all of the matching tool_result blocks together inside a single user message.



Mixed groups

A server tool grouped in parallel with a client tool still falls back to stop_reason tool_use.

Four tool_choice Values



auto

Claude decides whether to call a tool. This is the default whenever tools are provided.



any

Claude has to call one of the provided tools, though not a specific named one.



tool


Forces one specific named tool, useful when you know exactly which call you need.



none

No tools are called. This is the default when no tools are provided at all.

auto vs. Forced Calls



auto

Claude chooses whether and which tool to call, and can speak in prose before or instead of calling. It's the default.




any or tool

The API forces a call, so Claude emits no natural-language text first. Use auto plus an instruction if you want both.

Anthropic-Schema Client Tools

Some client tools come with a schema Anthropic defines, so you don't write it yourself.



bash, text_editor, memory, and computer_use are pre-typed

You still execute them in your own application

Claude returns tool_use, and you return the tool_result

Three Authoring Failures



Vague descriptions

A thin description misroutes, so Claude skips the tool or calls it for the wrong request.



Over-broad schemas

Loose types and open strings invite bad arguments the model fills with invented values.



Missing required fields

Leaving out a truly essential field lets the model omit it, so the call arrives incomplete.


Examples for Tricky Parameters

When a parameter is complex, a couple of input examples lift accuracy fast.

Examples show the model a valid, well-formed call

They clarify combinations a schema alone can't express

Each example has to validate against the schema



TOOL: search_flights
Parameter: date_range

Input examples for date_range

1
```
{
  "start": "2025-06-01",
  "end": "2025-06-07",
  "type": "fixed"
}
```


2
```
{
  "start": "2025-06-01",
  "nights": 5,
  "type": "nights"
}
```

3
```
{
  "month": "2025-06",
  "type": "flexible"
}
```

For unusual shapes, one good example beats a paragraph of prose.

A Definition Claude Calls Well

Bring it together, and a well-authored tool is easy for Claude to reach for.



A precise description that says when and when not to call

Clear purpose, the right use cases, and explicit boundaries help Claude decide with confidence.

A tight schema with narrow types and enums

Specific types and constrained enums reduce ambiguity and improve response accuracy.

Only the genuinely essential fields marked required

Keep required fields to the minimum so Claude can act quickly with less rejection and back-and-forth.

Tools Claude Calls Well



Claude returns tool_use, your code returns tool_result



tool_choice is auto, any, tool, or none



bash and text_editor are client tools you execute



Vague descriptions and over-broad schemas cause misfires



Examples lift accuracy on complex parameters

Client Tools versus Server Tools

When Claude calls a tool, the first question is who actually runs it.

Client Tools

Run in your application environment



Your Application

User Request → Claude → Client Tool (Runs locally in your app) → Result (Returned to Claude)

Example



Read local file



Calculate tax



Get local time



Bash execution

Server Tools

Run in Anthropic infrastructure



Anthropic Infrastructure

User Request → Claude → Server Tool (Runs securely on Anthropic) → Result (Returned to Claude)

Example



Web search



Web fetch




Code execution



Tool search

Three Terms to Anchor




Client tool

A tool that executes inside your application. Claude returns stop_reason tool_use and waits for you to run it and return a tool_result.



Server tool

A tool that runs on Anthropic's infrastructure. No handler of yours runs, and the result comes back directly in the response.



stop_reason tool_use

The response signal that Claude wants a client tool executed. It pauses the turn until you send back the matching tool_result.

Where Execution Happens



Client-side

The tool's code runs in your application. You receive `stop_reason` `tool_use`, execute the call yourself, and return a `tool_result` so the loop continues.



Server-side

The tool's code runs on Anthropic's infrastructure. You provide no handler and send no `tool_result`, because the result is already returned to you.

The Client Tool Round Trip

With a client tool, execution bounces between Claude and your own code.

Claude returns stop_reason tool_use with the tool name and input


Claude decides to use a tool and sends the request to your application.

Your application executes the tool and captures its output

Your code runs the tool, gets the result from the external system or API.


You return that output as a tool_result block

You send the tool_result back to Claude, which continues the conversation.



Then Claude reads the result and decides its next move.

Four Anthropic-Schema Client Tools



bash

Runs shell commands.
Anthropic supplies the schema, but the command executes in your environment.



text_editor

Views and edits files.
You run the actual file operations on your own system.



memory

Reads and writes persistent notes.
Your application performs the storage, not Anthropic.




computer_use

Controls a screen, mouse, and keyboard.
The actions run on your machine, not a server.

Server Tools Run on Anthropic Infra

Server tools execute on Anthropic's side, so you write no handler for them.



web_search and **web_fetch** pull in live web content

code_execution runs code in a hosted sandbox

tool_search finds relevant tools on demand

Results come straight back, with no tool_result from you.

The Parallel-Group Fallback

There's one case where a server tool behaves like a client tool.

It's grouped in parallel with a client tool call

The model returns both calls in the same step - client and server together.

The whole group falls back to stop_reason tool_use

Because a server tool is in the batch, the step ends immediately and yields tool_use.


Your loop then drives every call in that batch

Your application executes both the client tool(s) and server tool(s), then sends results back.

So a mixed batch always pauses for your code to run.




Three Runtime Consequences



You write fewer handlers

You only write execution code for client tools. Server tools need none, since Anthropic runs them for you.



Results arrive differently

Client results you assemble and send back. Server results appear inline, already attached to the response.



Tools still cost tokens

Providing any tools adds a standing tool-use system prompt cost, whatever tool_choice you set. The right-sizing lesson prices it out.

Choosing Which Kind to Reach For

Pick the tool type by what you need and who should run it.

Server Tool

Anthropic hosts it



- Runs in Anthropic's servers
- Ready to use
- No access to your private systems

OR

Client Tool

You run it



- Runs in your environment
- Access to your data and systems
- Fully under your control



Reach for a server tool when Anthropic already hosts the capability



Reach for a client tool to touch your own systems and data



Remember server tools can't see your private environment

Who Runs the Tool



Client tools run in your app, returning stop_reason tool_use



You execute them and send back a tool_result



Server tools run on Anthropic infra, with results returned directly



bash, text_editor, memory, and **computer_use** are client tools




A server tool in a parallel group falls back to tool_use

Errors, Approval, and Agentic Dispatch

Once tools run in a loop, three things decide whether it holds up.







Three Ideas in the Loop



Agentic dispatch

The model chooses which tool to call each turn. Your harness executes the choice and feeds the result back.



Execution loop

The cycle you run, inspect stop_reason, run the returned tool_use, append a tool_result, and re-invoke until Claude finishes.



Approval gate

A checkpoint that pauses a high-impact call for confirmation. It lives in your runtime, not in the model's judgment.

Agentic Dispatch in One Loop

In agentic dispatch, the model steers and your harness executes.




Claude selects the tool that fits the current step



Your code runs it and captures the observation




That observation goes back for the next decision



No hardcoded branch picks the tool. The model does.

Hardcoded Branch vs Agentic Dispatch



Hardcoded branch

Your code decides which function to call using fixed if-then logic. It's predictable but brittle, and blind to the context the model can read.



Agentic dispatch

Claude decides which tool fits each turn from the request and the tool descriptions. Your loop simply executes and feeds the results back.

Return Errors, Don't Crash

When a tool fails, hand the failure back to Claude instead of crashing the loop.



TOOL_RESULT PAYLOAD

```
{
  "type": "tool_result",
  "tool_use_id": "toolu_01",
  "content": "City not found: boston",
  "is_error": true
}
```

Put the error text in the tool_result content

Include the exact failure message inside the content field.

Set is_error to true so Claude sees it failed

The is_error flag signals the outcome without crashing.

Claude can then retry or adapt its approach


Claude can choose a different tool, fix inputs, or ask for clarification.

Three Kinds of Failure




Tool execution error

The tool ran and failed, a timeout or bad state. Return the reason in tool_result with is_error true.



Invalid parameter call

Claude sent arguments that don't work. Return an error and it retries with corrections, usually within a few attempts.



Server tool error

A server tool failed on Anthropic's side. Claude handles it transparently, so you return no is_error yourself.

Server Tool Errors Differ

Server tool errors don't flow through your error handling at all.



Claude catches them transparently on its side

Claude intercepts server tool errors and handles them before your code ever sees them.




You return no is_error for a server tool

Server tool results never include is_error = true - even when something goes wrong.



A web search may report rate limits or bad input

Server tools can fail for many reasons, like rate limits, invalid queries, or upstream issues.



Message-Format Rules That Bite

A few message-format rules cause silent 400 errors when you break them.



A tool_result has to immediately follow its tool_use

In the user turn, tool_result blocks come first, before any text

There's no separate tool role, results ride in user messages

Gating High-Impact Calls



Gate in the runtime

Pause sensitive calls in your loop and require confirmation before executing, not after the fact.



Use PreToolUse hooks

In the Agent SDK, a PreToolUse hook can inspect a call and block or allow it before the tool runs.



Keep it off the model

Don't rely on Claude to self-police high-impact actions. Enforce the gate in code you control.

Driving the Loop Safely



Return failures as tool_result with is_error true, don't crash



Write instructive error messages Claude can act on



Server tool errors are handled by Claude, not you




Agentic dispatch lets the model pick each tool




Gate high-impact calls in your runtime or a hook


Designing a Coherent Tool Set

A coherent tool set is one of the highest-leverage things you design for an agent.





The Triad, Applied to a Set




Name

billing_lookup labels the tool but names no action. In a set, the name has to separate it from its neighbors.



Description

A description like gets billing info gives Claude nothing to route on. Set design lives or dies on the when-to-use prose.



Input Schema

One open string invites invented arguments. Narrow types keep lookalike tools from blurring together.

Fewer, Well-Scoped Tools Win

A tool set is a menu the model reads on every turn, so keep it short and sharp.



Fewer, more capable tools
reduce selection ambiguity



Each tool should map
to one clear, predictable action



A sprawling surface makes
wrong-tool calls more likely



Add a tool only when
the task genuinely needs it

Focused Tool Menu

4 TOOLS



search_knowledge
Find answers in internal docs



analyze_sales
Compute metrics and trends



send_email
Send templated email



create_event
Schedule a meeting on the calendar

SIMPLE. PRECISE. EFFECTIVE.

Bloated Tool Menu

18+ TOOLS



CLUTTERED. RISKY. ERROR-PRONE.

Endpoint Wrapping vs. Agent Design



One Tool Per Endpoint

Mirrors your API surface directly, so the agent juggles many low-level calls to finish one task. A common error that floods the menu with near-duplicates.




Built for the Workflow

Designs tools around what the agent actually does. One tool can list, filter, and act under the hood, matching a realistic task in a single call.

Consolidate Related Actions

When several operations touch the same resource, fold them into one parameterized tool.



Prefer one tool with an action parameter over three near-duplicates

A single manage-pull-request tool beats create, review, and merge apart

Consolidation shrinks the menu and cuts selection ambiguity

The model reasons about one clear choice, not several overlapping ones

Fewer, more capable tools are far easier to route among.

Design Tools for Agents




Match Real Workflows

Build one tool that lists people and books a slot internally, not several raw endpoint calls chained by hand.



Compile Context

A single context-gathering tool collects everything the model needs at once, instead of many small reads.



Avoid Thin Wrappers

A tool that just wraps one API endpoint is rarely the right shape for an agent.

Describe When to Use, and When Not

The description is where you steer routing.



State what the tool does and when it should be used

Make the purpose, ideal use cases, and expected outcomes crystal clear.



Say explicitly when not to reach for it

List anti-patterns, risky contexts, and safer alternatives to prevent misuse.




Explain what each parameter means and how it changes behavior

Define types, defaults, ranges, and trade-offs for every input.



Write each line against the neighbors it competes with

Compare strengths, weaknesses, and decision rules versus similar tools.



Three Return Habits




High-Signal Output

Return only the fields Claude needs. Bloated responses waste context and bury the useful part.



Stable Identifiers

Return durable slugs or unique identifiers the model can reference later, favoring human-readable ones over cryptic codes.



Verbosity Controls

Offer concise versus detailed response modes so the caller pulls only as much as the task needs.

Prove It With Evaluations

You cannot tell a good tool set from a bad one by reading it. Measure it.

EVAL DASHBOARD

Last 7 days

ACCURACY	TOOL CALLS	TOKENS	RUNTIME
87.4%	342	1.26M	2.31m
↑ 6.2%	↓ 12.4%	↑ 9.1%	↓ 8.7%

ACCURACY OVER TIME



LATEST RUN SUMMARY

TASK ID	DESCRIPTION	TOOLS USED	ACCURACY	TOKENS	RUNTIME
T-1021	Q2 revenue + YoY growth by region		92%	18,432	1.42m
T-1020	Top 10 support tickets by category		84%	12,915	1.18m
T-1019	Customer churn risk analysis		78%	24,109	2.05m



Build realistic multi-tool tasks and run the agent against them



Track accuracy, tool-call count, tokens, and runtime



Read reasoning transcripts to spot ambiguous descriptions



Fix the wording, then re-run and compare

What a Coherent Tool Set Looks Like



Fewer, well-scoped tools route better than a sprawling surface



Consolidate related actions behind one parameterized tool



Design tools for agent workflows, not one per API endpoint




Descriptions carry the when-to-use and when-not signal




Evaluations tell you whether the set actually works

Naming, Overlap, and Tool Count

How you name, scope, and count your tools shapes whether an agent routes reliably.





Name Tools So Routing Is Obvious

Names are the first thing the model scans, so make each one unambiguous.

Give every tool a distinct, action-oriented name

Names should describe a clear action, not an object or vague intention.

Namespace with the service when tools span systems

Prefix tool names with the service so the model knows where to route.

Prefer billing_list_invoices over a bare list that could mean anything

Be specific so the model picks the right tool every time.

Consistent service_resource patterns cut confusion

Use the same naming pattern across all services and tools.

Example Tool Namespace Design


billing	billing_list_invoices	billing_get_invoice
	billing_create_invoice	billing_refund_payment
users	users_list_customers	users_get_customer
	users_update_customer	users_deactivate_customer
orders	orders_list_orders	orders_get_order
	orders_create_order	orders_cancel_order
email	email_send_message	email_get_message
	email_list_messages	email_mark_as_read
inventory	inventory_list_items	inventory_get_item
	inventory_update_stock	inventory_adjust_stock

Distinct vs. Overlapping Tools



Distinct Tools

Each tool owns one clear job, and their descriptions don't compete. The model maps a request to exactly one obvious choice.



Overlapping Tools

Two tools whose descriptions blur together. The model mis-selects, especially when the names look similar, and calls the wrong one.

Three Sources of Misrouting



Similar Names

When two tools read almost the same, the model confuses them and picks the wrong one under pressure.



Competing Descriptions

Overlapping descriptions give the model no clean way to tell which tool fits the request.



Vague Scope

A tool that tries to do everything matches too many requests, so it fires when a sharper tool should have.

Every Tool Costs Tokens

Tools aren't free. Providing them injects a tool-use system prompt into every request.



On Opus 4.8, providing tools adds roughly 290 tokens of overhead



Names, descriptions, and schemas all count as input tokens



Even tool_choice none pays this cost once tools are present



The truly zero-token case is providing no tools at all


A big tool set spends context before the conversation even starts.

When to Prune a Tool



Rarely Correct

If evals show a tool is seldom the right call, its cost and ambiguity outweigh its value.



Redundant

If another tool already covers the action, fold them together and drop the duplicate.



Unused Surface

Every extra tool widens the attack surface, so cut what the task doesn't need.

Scaling to Large Tool Sets


Some agents need dozens of tools, and loading them all up front burns context.

The Tool Search Tool
lets Claude discover tools on demand

Mark rarely-used tools
defer_loading true so they load when needed

Keep the few most-used tools
always loaded

This trims the up-front
token cost of a large surface




Discovery on demand keeps a big set from crowding the context window.

Three Scaling Levers



Tool Search

The on-demand discovery you just saw. It's the baseline the next two levers build on.



Programmatic Calling

Lets Claude orchestrate tools through code, keeping intermediate results out of the context window.
First-party API only.




Tool Use Examples

Attaching example inputs to a tool improves accuracy when its parameters are complex.

When to Reach for MCP

Not every tool belongs in one app.



Keep app-specific tools as plain custom tools

Package a set behind an MCP server when many clients reuse it

MCP gives one standardized, model-agnostic integration

Shared reuse, not raw count, is the reason

Right-Sizing the Tool Surface



Distinct, namespaced names keep routing unambiguous



Overlapping or vaguely scoped tools cause mis-selection



Every provided tool spends system-prompt tokens



Prune rarely-correct tools and defer-load large sets




Reserve MCP for capabilities shared across clients

MCP Primitives and Who Controls Them

An MCP server exposes three primitives, but the trap isn't what they are, it's who controls each one.


WHAT THE MCP SERVER EXPOSES




Example: tools/list result

```
{
  "tools": [
    {
      "name": "get_weather",
      "description": "Get current weather for a location",
      "inputSchema": { "type": "object", "properties": {
        "location": { "type": "string" },
        "unit": { "type": "string", "enum": ["celsius", "fahrenheit"] }
      } },
      "outputSchema": { "type": "object", "properties": { "temp": { "type": "number"},
        "unit": { "type": "string" }, "condition": { "type": "string" } } }
    }
  ]
}
```

WHO CONTROLS EACH PRIMITIVE



Three Server Primitives




Tools

Executable functions the model may call, such as an API request or a database query. They are the actions an MCP server exposes to Claude.



Resources

Read-only data sources like file contents, records, or API responses, each identified by a URI. They supply context, they never perform actions.



Prompts

Reusable templates a user explicitly selects, usually surfaced as slash commands or menu items in the host application.


Ownership Is the Whole Game

Every primitive answers to a different controller, and mixing them up is the top MCP mistake.


Tools are model-controlled,
the model decides to call them

Resources are
application-controlled,
the host injects them

Prompts are
user-controlled,
the human selects them



Who Controls Each Primitive




Tools: model

The model discovers and invokes tools on its own, reading the request and the tool's description.



Resources: application

The host application decides which resources to pull in as context, on its own terms, not the model.



Prompts: user

A person picks a prompt template deliberately, so the model never triggers one by itself, ever.

Tools Are Model-Controlled

A tool is a callable action, and the model chooses when to fire it.






The model discovers the tools a server advertises

The model inspects the server's tool list and understands their names, descriptions, and parameters.



It invokes them from context and the user's request

Based on the conversation and goal, the model selects a tool and supplies the right arguments to run it.



Each tool wraps an API call, a query, or a file operation

Tools perform real work - calling APIs, querying databases, or reading/writing files - and return the results.


Resources Are Application-Controlled

A resource is read-only context, and the host application decides how to use it.

Each resource is named
by a URI the client can read

The host injects the data,
the model never fetches it


Files, database records,
and API responses all fit here




Because resources only supply data, they never carry out an action.

Prompts Are User-Controlled

A prompt is a reusable template, and the user is the one who reaches for it.





Servers expose prompts for a person to select




Hosts often surface them as slash commands or menu items



The model does not trigger a prompt on its own

inputSchema vs. input_schema



inputSchema (MCP)

In the MCP protocol a tool declares its parameters with inputSchema, written in camelCase. You will also see isError and tools/call in the same style.



input_schema (API)

The Claude Messages API uses input_schema in snake_case, alongside is_error and tool_use. Same ideas, different layer, so do not conflate the spellings.

MCP Is an Open Standard

MCP is an open, model-agnostic standard, not a Claude-only feature or a single API.

One server can serve many compliant clients


A single MCP server can be consumed by any number of MCP-capable clients.

The same tools and resources reuse across hosts

Tools, prompts, and resources are defined once and reused by every connected client.

Any client that speaks MCP can connect to it

Language, framework, or platform don't matter - interoperability comes from the standard.



That standard interface is what a plain function-calling API does not give you.

Match Primitive to Controller



Tools are model-controlled callable actions




Resources are application-controlled read-only data



Prompts are user-controlled selectable templates



MCP uses inputSchema, the Claude API uses input_schema



One standard server serves many clients

Authoring and Registering a Server

With the three primitives clear, the next step is building a server that actually exposes them.

MCP Server

Author

Tools

```
{
  "name": "get_weather",
  "description": "Get weather",
  "inputSchema": { ... }
}
```

Resources

```
{
  "uri": "weather://alerts",
  "mimeType": "application/json",
  "name": "Severe Alerts"
}
```

Prompts

```
{
  "name": "trip_planner",
  "description": "Plan a trip",
  "arguments": [
    {"name": "destination"},
    {"name": "days"}
  ]
}
```

Register


```
initialize result
{
  "protocolVersion": "2025-06-18",
  "capabilities": {
    "tools": {},
    "resources": {},
    "prompts": {}
  },
  "serverInfo": {
    "name": "weather-mcp",
    "version": "1.0.0"
  }
}
```

Register Capabilities

- ✓ tools
- ✓ resources
- ✓ prompts

Server Ready

Exposes capabilities over MCP



Three Primitives to Register



Tools

Registered with a name, a description, and an inputSchema, then invoked through the tools/call method the client sends.



Resources

Registered with a URI and served read-only through resources/read, so the host can pull them in as context.



Prompts

Registered with a name and optional arguments, then returned as messages when the client sends prompts/get.


Registering a Tool

On the server, each tool is a definition the client can discover and call.

Give it a name, a description, and an inputSchema

Optional fields add a title, an outputSchema, and annotations

Clients discover tools via tools/list, then run tools/call



Prefer a namespaced name like calculator_arithmetic over a bare calculate.

Discovery vs. Execution



Discovery

Every primitive offers a list method, tools/list, resources/list, or prompts/list, so a client can find out exactly what the server exposes before using it.




Execution

Retrieval and action are separate calls, so tools/call runs a tool, resources/read returns data, and prompts/get, returns a filled template.


Registering a Resource

A resource is read-only data that the application can inject as context.





Identify each one with a unique URI the client addresses



Serve them through `resources/list` and `resources/read`



Optional fields include a name, description, and mimeType

Four Authoring Concerns



Capability declaration

At startup the server announces which primitives it supports, so clients know what to expect.



Request routing

Incoming list, read, and call methods get dispatched to the right handler on the server.



Response formatting

Each handler returns results in the shape the protocol defines, as content the client can use.



Error signaling

Protocol errors and tool-execution errors are reported differently, so failures stay clear.

Registering a Prompt

A prompt is a template the user selects, exposed by the server for people to choose.



Declare a name and an optional list of arguments

You define the prompt's identity and any parameters clients can provide when requesting it.




Clients list prompts, then fetch one with prompts/get

Clients discover available prompts and retrieve the one they want to use by its name.



The server returns a set of messages to seed the conversation

The server responds with a message list that initializes the conversation for the model.



isError vs. is_error



isError (MCP)

An MCP tool result reports a failed execution by setting isError to true, spelled in camelCase, matching inputSchema and tools/call on the JSON-RPC wire format.




is_error (API)

The Claude Messages API signals the very same failure with is_error, in snake_case, beside tool_use and input_schema. Same idea, different layer, different spelling.

Roots Are Advisory Scope

Roots tell a server where to focus. They do not build a wall around it.



Roots name
the filesystem paths or URIs a client puts in scope

They are advisory,
well-behaved servers should respect them

A local stdio server
still runs with its OS user's full file access

Building a Server That Serves



Register tools, resources, and prompts with the server



Discover with list, then call, read, or get



Declare capabilities, route requests, format responses




MCP uses isError, the Claude API uses is_error




Roots are advisory scope, real isolation is OS-level

stdio Transport for Local MCP Servers

An MCP server has to talk to its client somehow,
and the transport is the channel that carries every message.




Host, Client, and Server



Host

The AI application, such as Claude Code or Claude Desktop, that coordinates one or more clients and runs the whole experience.



Client

A component inside the host that holds one dedicated connection to one server. The host creates one client per server.



Server

A program that provides tools, resources, and prompts. It runs locally as a subprocess or remotely as a service.


One Client Per Server

The host is the hub, and it opens a separate client for every server it uses.



Each client

keeps exactly one
connection to one server




The host

runs many clients
when it uses many servers




No single client

fans out to
multiple servers



Data Layer vs. Transport Layer



Data layer


The protocol itself, built on JSON-RPC 2.0. It defines the connection lifecycle, the primitives like tools and resources, and the exact shape of every message exchanged.



Transport layer

The channel that actually carries those messages between the two sides. It handles framing and delivery. stdio and Streamable HTTP are MCP's two standard transports.

How stdio Moves Messages



stdin

The client writes JSON-RPC requests to the server's standard input, one message per line.



stdout

The server writes its JSON-RPC responses back on standard output, and nothing else belongs there.



stderr

The server may send logs and diagnostics to standard error, kept separate from the message channel.

The Newline-Delimited Rule

stdio messages are newline-delimited, so clean line boundaries are what keep the stream parseable.

STDIN (client -> server requests)

```
{"jsonrpc":"2.0","id":1,"method":"initialize","params":{"capabilities":{"roots":{}}}}
\n
{"jsonrpc":"2.0","method":"tools/list","id":2}
\n
{"jsonrpc":"2.0","method":"tools/call","id":3,"params":{"name":"get_weather"}}
```

STDOUT (server -> client responses)

```
{"jsonrpc":"2.0","id":1,"result":{"serverInfo":{"name":"demo-server"}}}
\n
{"jsonrpc":"2.0","id":2,"result":{"tools":[{"name":"get_weather"}]}}
```



Each message is one line with no embedded newlines

A single JSON object per line keeps parsers simple and reliable.



Only JSON-RPC belongs on stdout, nothing else

No banners, prints, or debug output should ever appear on stdout.



Logs and diagnostics go to stderr instead

Keep stderr for human-readable logs and diagnostics.

STREAMING CALL (TEXT DELTAS)

```python
from anthropic import Anthropic
client = Anthropic()
with client.messages.stream(model="claude-opus-5", max_tokens=1024, messages=[{"role":"user","content":"Hello"}]) as stream:
    for text in stream.text_stream:
        print(text, end="", flush=True)
```

Three stdio Traits




Local by design

Client and server share one machine, so there is no network hop. That gives stdio low latency and very simple setup.



Single client

A stdio server typically serves one client at a time, which fits local, single-user developer tooling.



Subprocess lifecycle

The client launches the server as a child process and manages its lifetime, starting it and shutting it down.

When stdio Is the Right Fit

Reach for stdio when the server lives on the same machine as the application using it.

Local developer tooling and command-line integrations


Connect your app to powerful local tools through simple standard input and output streams.

Single-user setups where no one remote connects


Everything runs on your machine for you alone - no remote access or multi-user concerns.

Cases where you want zero network overhead

Avoid sockets, HTTP, and latency. stdio is the fastest path between your app and local tools.



Credentials Without OAuth



stdio credentials

A local stdio server reads whatever credentials it needs from the environment, such as environment variables the client sets before launching it.



No OAuth here

The OAuth flow does not apply to stdio at all. Authorization is defined only for the HTTP-based transport, which the next lesson covers in depth.

stdio for Local Servers



The host runs one client per server



The client launches the server as a child process



Messages are newline-delimited on stdin and stdout



stdio fits local, single-user setups



Credentials come from the environment, not OAuth

Networked MCP: Sockets, HTTP, and Auth

When an MCP server runs elsewhere and serves many users, stdio no longer fits. You need a networked transport.

This lesson covers Streamable HTTP, MCP's standard remote transport, the setup loosely called sockets.

It also covers the OAuth 2.1 flow that proves a remote client's identity before it uses the server.




Streamable HTTP Basics




Independent process

The server runs on its own, not as a child of the client.
It can serve many clients at once over the network.



Single endpoint

One MCP endpoint path, such as slash mcp,
handles the traffic. It supports both POST and GET requests.



Streaming capable

The server can reply with one JSON object or open
a stream to send several messages back over time.

One Endpoint, POST and GET

Every message flows through a single MCP endpoint that speaks two HTTP methods.




The client POSTs
each JSON-RPC message
to the endpoint



It sends an Accept header
for JSON and
event streams



An optional GET
opens a stream for
server-initiated messages



The server answers with one JSON reply or an open event stream.

Two Session Headers



Mcp-Session-Id

The server may assign this identifier on the initialize response. From then on, the client echoes it on every later request so the server can track the session.



MCP-Protocol-Version

After initialization, the client sends this header on subsequent requests so both sides agree on exactly which revision of the protocol they are speaking.

Streamable HTTP vs. Old SSE



Streamable HTTP

The current remote transport, introduced in 2025. One endpoint handling POST and GET, with optional streaming. This is what new servers build on today.




Deprecated HTTP+SSE

The older 2024 transport used a separate Server-Sent Events channel for streaming. Streamable HTTP replaced it, so it should not anchor new work.

Guarding the HTTP Endpoint

A networked endpoint is exposed, so the spec builds in a few defenses.



The server validates the Origin header to block DNS rebinding

When it runs locally, it binds to 127.0.0.1 only

It authenticates clients before serving any tools

An open, unauthenticated endpoint is an invitation you don't want to send.

Three OAuth Roles



Resource server

The MCP server itself. It validates the access token on every request and serves its tools only to valid callers.



OAuth client

The MCP client. It obtains a token and attaches it to each request it sends to the server.



Authorization server

A separate party that issues the tokens. It can be co-hosted with the server or run independently.

Token Handling Rules



Bearer header

The access token rides in the Authorization header as a bearer token on every request.



Never in the URL

The token is never placed in the query string, where URLs get logged and cached.



Audience check

The server confirms the token's intended audience matches this server before honoring it.



No pass-through

The server does not forward your token to upstream APIs, closing a confused-deputy risk.

Local vs. Remote, Side by Side



Local, stdio

One client and a server running as a child process on your own machine, with credentials pulled from the environment. There is no network identity to prove.



Remote, HTTP

Many clients reaching an independent networked service, where each client authenticates with OAuth 2.1 and proves who it is before any tool is served.

Networked MCP and Auth



One endpoint handles POST, GET, and streaming



It replaced the deprecated HTTP and SSE transport



The server validates Origin and binds to localhost when local



Auth is OAuth 2.1, defined for HTTP only



The token rides in a Bearer header

Extending Claude Beyond Text

Claude can do far more than generate text once you give it capabilities, and there are four different ways to do that.

Four Ways to Extend Claude



Built-in Tools

Web search and code execution



Custom Tools

Functions you define and run



Skills


Packaged instructions and files



MCP Servers

Connect external systems

Example: Market Research Agent




Four Ways to Extend




Built-in tools

Ready-made capabilities Anthropic hosts for you, like web search and code execution, used with no handler code.



Custom tools

Functions you define and run yourself to give Claude one action specific to your own application.



Skills

Reusable instructions and workflow packaged in a SKILL.md file, loaded only when the task matches.



MCP servers

Tools, resources, and prompts exposed over a standard interface, reusable across many clients and teams.

Built-in Tools: Ready-Made

Built-in tools, also called server tools, run on Anthropic's own infrastructure.

You write no handler code, and results return directly


No glue code. Results flow back automatically from Anthropic.

web search, web fetch, code execution, and tool search are the core set

These built-in tools cover the most common external actions.


They cannot reach your private systems or internal APIs

Built-in tools run in Anthropic's environment only.



Custom Tools: You Build and Run

A custom tool is a function you define and execute in your own application.



Claude requests the call, and you return the real result.

You write the name, description, and input schema

Define exactly what the tool is and what it expects.

Your code runs the call, so it reaches anything your app can

Your application handles auth, network, and business logic.

This is how you connect Claude to internal systems and data

Query databases, call APIs, or use any capability your app has.

Built-in vs. Custom Tools



Built-in tools

Run on Anthropic's infrastructure with no handler to write. Effortless to adopt, but limited to hosted capabilities and unable to reach your private data.



Custom tools

Run in your application, so you write and execute them. More effort, but they reach any internal system your own code can access.

What a Skill Packages



SKILL.md

The file at a Skill's root. Its frontmatter carries a name and description, followed by the instructions Claude should follow.



Description trigger

The short summary Claude reads each turn. The full Skill loads only when the task matches it.



Progressive disclosure

Metadata first, full content only when relevant, so a Skill's bulk stays out of context until needed.

Skills: Procedural Knowledge

A Skill captures a workflow you want carried out the same way every time.



It packages steps, conventions, and formatting as reusable know-how



Claude pulls it in only when the task matches its description



On the Claude API a Skill makes no external network calls

For live data, it pairs with a tool or an MCP server.



MCP: A Shared Standard

MCP is an open standard for connecting Claude to external tools and data.



It is not a model and not a single API endpoint

MCP is a protocol, not a model.
It is not tied to any vendor or path.

One server packages tools, resources, and prompts behind a uniform interface

Servers expose capabilities consistently, no matter what they connect to.

Any compliant client can use it, so you integrate once

Build once on MCP and connect to many systems.

Reach, Reuse, and Context



Reach

Whether a mechanism can touch your private systems. Built-in tools can't, while custom tools and MCP servers can.



Reuse scope

Whether the capability serves one application or is shared across many clients and teams.



Context cost

How much a mechanism consumes before the conversation starts. Progressive disclosure keeps Skills cheap.

The Four Mechanisms at a Glance



Built-in tools are hosted but can't reach private data



Custom tools you define and run for app-specific actions



Skills package reusable workflow, loaded on demand




MCP servers expose a standard, shareable integration

Choosing the Right Extension Mechanism

With four ways to extend Claude available,
the real skill is choosing the right one for a given need without overbuilding.





Start With the Lightest Fit

The guiding rule is simple. Pick the lightest mechanism that does the job.



Every mechanism
adds context cost or
infrastructure to maintain



Reaching for an MCP server
when a custom tool
fits is overbuilding



Start simple
and move up only
with a concrete reason




Built-in first, then custom, and only then Skills or MCP.

Three Questions to Ask



Does a built-in cover it?

If Anthropic already hosts the capability,
use the built-in tool and go no further.



Is it one app's action?

If the need is specific to a single application,
a custom tool is the right size.




Does it need reuse?

If a capability is shared across clients or teams,
reach for a Skill for procedure or MCP for system access.

Reach for Built-in First

Built-in tools cost the least, so try them first when they cover the need.



No handler to write, no server to run or maintain

Use built-in tools without implementing handlers or operating infrastructure.

web search, web fetch, code execution, and tool search cover common needs

These four tools solve most information gathering, retrieval, execution, and discovery tasks.

Their ceiling is your firewall, since they run on Anthropic infra

Built-in tools operate within Anthropic's safety, privacy, and reliability boundaries.

When the job needs private data, move to the next option.

Custom Tool for One App's Action

When a built-in can't reach far enough, a custom tool is usually the answer.

You give Claude one well-defined, app-specific action


You design a focused capability that does exactly one thing your app needs.

You write the schema and run the handler yourself


You define the tool's inputs and outputs, then implement and deploy the handler.

It reaches whatever your own code can reach

Your tool can call internal APIs, private services, or perform any logic you trust.




Skills vs. MCP



Skills

Package procedural knowledge. A Skill teaches Claude how to carry out a workflow, its steps and conventions, done the same way every time.




MCP

Provides connectivity. It is the standardized wiring that gives Claude access to external tools, resources, and data, all behind one shared interface.

Skills and MCP Work Together

Skills and MCP are complementary, not competitors you choose between.



An MCP server brings the reach to external systems

A Skill brings the method, which tool to call and when


Progressive disclosure keeps the paired Skill cheap on context

What Drives the Choice




Reach

Does the capability need systems Anthropic doesn't host? If so, built-in is out, leaving custom tools or MCP.



Reuse scope

One application points to a custom tool. Shared connectivity points to an MCP server, shared procedure to a Skill.



Context cost

Heavier mechanisms consume more context, which is why you don't reach for them by default.

Combining Mechanisms

A real agent often uses several of these at once, not just one.

A built-in tool, a custom tool, an MCP server, and a Skill can coexist


Agents combine native capabilities with custom logic, external resources, and specialized skills.

The framework is applied per capability, not once for the whole agent

Each capability can use the mechanism that best fits its needs and constraints.

Different needs land on different mechanisms

Routing uses the simplest effective option that reaches the desired outcome safely and reliably.



Picking the Right Extension



Built-in tools when Anthropic already hosts the capability



Custom tools for one application's specific action




Skills for reusable procedure, MCP for shared connectivity




Skills and MCP complement each other, so combine them

Before Your First Practice Exam


The first major block of C.C.D.V.-Foundations material is behind you. Quick pause before the practice exam.





What You've Built So Far

You have a working understanding across the C.C.D.V.-F. domains.



Agents and workflows, the A.P.I., tools and M.C.P., security, model selection, and more

Knowing the material and passing an applied exam are different skills

Practice exams test recognition under pressure, not recall

The course built the foundation. Practice exams build the judgment.


How Practice Exams Are Different

Same question pool as the lesson quizzes, but the experience shifts.

In lessons, a question lands right after the topic that supports it

On a practice exam, it shows up alongside every other domain


You recall the reasoning on your own, without the lesson framing it



CCDV-F is an applied exam. Judgment matters more than memorization.

What to Expect on Your First Try

Most developers score in the fifties to mid-sixties on the first practice exam.




Completely expected.
Progressive difficulty by design

The first test exposes gaps,
it does not validate readiness

The goal is finding exactly
where your understanding breaks down

After Your First Practice Exam

Practice complete. The fact that you're here reviewing means you're doing this the right way.



Lean Into Practice

Commit the same energy to practicing that you spent learning.

Each practice exam should take under two hours. Focused sessions, not marathons

A strong score on an easy exam does not mean exam-ready

A full set of graduated practice exams is available here. Same style, fresh questions



Repetition builds the judgment you need for unfamiliar exam scenarios.

Your Review Methodology

This is where most of the real learning happens at this stage.


Start with every answer you got wrong.
Read the explanation, understand the why

Review every answer you guessed on,
even the correct ones

Leave the confident-correct answers alone.
Your review time is valuable

METHODICAL ANALYSIS CHECKLIST

A systematic review process



What Happens Next

The second practice exam is harder by design.



New scenario types,
deeper build-and-integrate tradeoffs

Your score should improve,
but don't expect a dramatic jump

Watch the type of mistakes.
Same as before, or new ones?


You've Completed CCDV-Foundations

End of the course. You've worked every domain, taken practice exams, and reviewed your results.



Keep Pushing on Practice

Practice exams are the highest-return activity between now and exam day.





Every practice exam sharpens judgment, timing, and scenario fluency



A full set of graduated practice exams is available here, fresh questions



You will be back each renewal window, and the practice library scales with you

No diminishing returns. The more reps you put in, the better your odds.

Renewal Is Built In

Your enrollment covers every renewal cycle going forward.



The course updates continuously as the C.C.D.V.-F. outline evolves



Each year, watch the updated lessons and take the free renewal assessment



No extra purchase. One enrollment, current forever



Before You Go

Thank you for sticking with this course. CCDV-Foundations is a real commitment.



Collect your course completion certificate. It qualifies for C.P.E. credits in many programs

Connect with me on LinkedIn, and tag me when you pass. I celebrate every win

Keep building. The best exam prep is shipping real Claude applications